

DoP (declaration of performance)

Declaration of performance

Nr. 924.1.1

924 EUROPLAN HYBRID

1. Unique identification	Each package is labelled with a unique batch number that can be traced back to the specifications drafted for this levelling mortar.	
2. Designation	Forbo Eurocol 924 Europlan Hybrid; Self-levelling compound, tension-free curing for both calcium sulphate and cementitious subfloors.	
3. Application	For levelling in coatings from 2 tot 10 mm of cementitious and anhydrite-bound subfloors, mastic asphalt, magnesite, wood granite, chipboard or existing tiling.	
4. Name and contact address manufacturer	Forbo Eurocol Nederland B.V. Industrieweg 1-2 NL-1521 NA Wormerveer The Netherlands Tel. +31 75 6271600 Email: info.eurocol@forbo.com	
5. Name and contact address authorized	n/a	
6. System of assessment and verification of constancy of performance	4	
7. Activity of the notified certification body as required by the harmonized standard	n/a	
8. European Technical Assessment	n/a	
9. Declared performance	CA-C50-F10 In accordance with NEN-EN 13813:2002 Self-levelling compound, tension-free curing for both calcium sulphate and cementitious subfloors.	
Essential characteristics	Performance	Test method
Tensile strength after 28 days	F10	NEN-EN 13892-2:2002
Compressive strength after 28 days	C50	NEN-EN 13892-2:2002
Material behaviour in case of fire	Class F	NEN-EN 13501-1:2007+A1:2009
Released dangerous substances	see MSDS	
Declaration drafted in accordance with Annex ZA of NEN-EN 13813: 2002		
10. The performance of the points 1 and 2 are consistent with the described product specified in paragraph 9 performance. This declaration of performance is issued under the sole responsibility of the in item listed manufacturer 4.		
		Wormerveer, 03-05-2019 signed: ing. T.W. Breeuwer; Manager R&D 