

eurocol

891

the strong connection

EUROCLEAN BASIC

Universal basic cleaner and also suitable for linoleum.

PRODUCT TYPING

Base	Water-soluble tensides.
Color	Transparent.
Consistency	Thin liquid.

- Water-based basic cleaner for basic or intensive cleaning and decoating of suitable, resilient floor coverings (PVC, CV, elastomeric flooring, linoleum, sealed parquet) as part of regular cleaning work.
- Removes stains, footprints, soiled wax residues and worn polymer layers on waterproof floor coverings or other smooth surfaces.
- For the removal of fixation residues from dense surfaces.
- Can be diluted with water.
- Request instructions for the different types of floor coverings!

PROPERTIES

Consumption	depending on degree of dirtiness, approx. 15 - 70 m ² /litre.
Flammability	Non-flammable.
Frost resistance	No.
Special quality	pH 8 - 9, suitable for Linoleum.
Specific weight	Approx 1.0 kg/l.

APPLICATION

Basic cleaner for general or intensive cleaning of water-resistant surfaces.

PROCESSING

Storage	Store cool and free from frost (5°- 30 °C).
Tools	Wiper, cleaning pads.
Mixing ratio	Approx 1 : 5 with cold water.
By drying	12 - 24 hrs.
Shelf Life	Minimum 36 Months, in unopened packaging.
Cleaner	Water.

** The stated values are laboratory values which, given the large variation in climatological conditions, subfloor compositions and layer thicknesses, are only guideline values.*

Substrate:

- Test the colourfastness of the surface/covering in a concealed area before use.

891 EUROCLEAN BASIC

- The sealing of parquet and cork floors must be completely closed.
- Coarse dirt must first be removed by sweeping or vacuuming.

Instruction manual:

- Moisten the floor with clear water.
- Use 891 Euroclean Basic undiluted or dilute up to 1:5 with cold water, depending on the degree of dirtiness / thickness of the polymeric coating to be removed.
In case of very old coatings, use undiluted or repeat the cleaning process.
- Spread the solution on the floor. Use a spray can or mop. Leave on for approx. 10 minutes, but do not let it dry.
- Loosen stubborn dirt with a brush or suitable pad, immediately remove dissolved dirt with the dirt liquor using a wet Hoover or cloth / mop.
- On stubborn fixation or adhesive residues that are not older than a few days, apply diluted 1:1 or, if necessary, concentrated. In case of old fixation residues, apply several times undiluted or let it work for a longer time, if necessary cover with film overnight. Remove the swollen adhesive residues mechanically, if necessary using cleaning machines.
- Finally, wipe twice with clear, cold water to remove all residues, wipe the floor dry.
- All thoroughly cleaned surfaces, especially parquet floors / floor coverings, must be re-applied after intensive cleaning. The floor must be completely dry before being treated (see care instructions for the floor covering, approx. 12 - 24 hours).

ENVIRONMENT AND HEALTH

GISCODE	GG60
Hazard Class	Product contains hazardous ingredients. Please observe the notes in the Safety data sheet!
Safety and environment	Safety data sheets of Forbo Eurocol products according to EEG-guideline 91/155. Keep out of reach of children. Do not eat, drink or smoke while processing the product. Only give completely empty containers for recycling. Material residues can be disposed of as household waste.
MSDS	For extensive information about safety and environment we refer to our website www.forbo-eurocol.de .

ITEM DATA

artikel	productname	packaging	shipping unit
891	Euroclean Basic	PE jerrycan à 10 l	60/pallet
891	Euroclean Basic	PE jerrycan à 2,5 l	8/box 120/pallet

Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed. This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work. The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturers liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content. As use, processing- and storage conditions on site are beyond manufacturers influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to be followed by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use.

This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!

BG175070, Version V09, Stand 2023-03-13, ersetzt Version vom 2019-05-14.

891 EUROCLEAR BASIC