

1. Unique identification	Each package is labelled with a unique batch number that can be traced back to the specifications drafted for this adhesive.	
2. Designation		
3. Application		
4. Name and contact address manufacturer	Forbo Eurocol Nederland B.V. Industrieweg 1-2 NL-1521 NA Wormerveer The Netherlands Tel. +31 75 6271600 Email: info.eurocol@forbo.com	
5. Name and contact address authorized	n/a	
6. System of assessment and verification of constancy of performance	3	
7. Activity of the notified certification body as required by the harmonized standard		
8. European Technical Assessment	n/a	
9. Declared performance		
Essential characteristics	Performance	Test method
Initial adhesive strength	> 1 N/mm ²	NEN-EN 1348:2008 §8.2
Adhesive strength after water exposure	> 1 N/mm ²	NEN-EN 1348:2008 §8.3
Heat exposure	> 1 N/mm ²	NEN-EN 1348:2008 §8.4
Adhesive strength after water exposure and freeze/thaw	> 1 N/mm ²	NEN-EN 1348:2008 §8.5
Open time 20 minutes	> 1 N/mm ²	NEN-EN 1346:2008
Material behaviour in case of fire	Class E	NEN-EN 13501-1:2007+A1:2009
Released dangerous substances	see MSDS	
Optional characteristics	Performance	Test method
Increased sagging resistance	≤ 0.5 mm	NEN-EN 1308:2008
Extended open time 30 minutes	≥ 0.5 N/mm ²	NEN-EN 1346:2008
Flexibility	S1 (> 2,5 mm en <5 mm)	NEN-EN 12002:2008
Declaration drafted in accordance with Annex ZA of NEN-EN 12004:2007+A1:2012.		
10. The performance of the points 1 and 2 are consistent with the described product specified in paragraph 9 performance. This declaration of performance is issued under the sole responsibility of the in item listed manufacturer 4.		
		Wormerveer, 25-07-2023 signed: ing. T.W. Breeuwer; Manager R&D 