nuway® tuftiguard

TECHNICAL SPECIFICATIONS

Tuftiguard plain Tuftiguard classic Tuftiguard design

Maximum length per module	2500mm (Bamboo 2400mm)																
Maximum width per module	750mm																
Maximum weight per module	23kg/m ²																
Depth	12mm	12mm							17mm								
Scraper bar material	Silver, black, sand, bronze or gold anodised aluminium				Bamboo				Silver, black, sand, bronze or gold anodised aluminium				Bamboo				
Construction	Open		Closed		Open		Closed		Open		Closed		Open		Closed		
Number of wiper strips	1	2	1	2	1	2	1	2	1	2	1	2	1	2	1	2	
Total weight (kg/m²)	11	12	14	15	10	11	13	14	14	15	16	17	13	14	15	16	
Max static load (kg/cm²)	200				100				200				200				
Dynamic load (kg) 2 wheels 80mm, 20,000 passes	200				100				200				200				
Frames	A selection of recessed matwell frames are available																
Ramp frame model	ARF 50	ARF 50								ARF 70							
Manufacturing method	Entran	Entrance flooring system with scraper bars and rubber wiper strips															
Wiper designs	Plain, r	natural f	bres, col	oured fib	ores												
Wiper material	Rubbe	r															
Pile material	100%	Polyami	de BCF														



CONSIDERATIONS

Bamboo is a natural product so there will be a variance of colour within the scraper bars and although the Bamboo may fade and lose small 'splinters', the structural integrity of the mat will not be affected.

In very brightly lit areas, the strong contrast between a light aluminium scraper bar and a dark wiper strip can sometimes create a strobe effect, which should be avoided.

To prevent this type of occurrence, consider using scraper bars in **Bamboo** or **Anodised Aluminium**.

