

### E 4/2 U0/U/S2 HACCP-FF white FDA



Sketch of cross-section (not actual size)

#### Applications

- Incline and decline conveying
- Conveying of sticky goods
- Confectionary processing
- Meat processing, e.g. filling-flow-divider
- Cooling conveyors
- Packaging, e.g. wrapping

#### Properties/Advantages

- Longitudinally flexible fabric => tight transfers with small pulleys
- Urethane intermediate layer => easy splicing, robust splice
- Combined overlap Z-splice possible
- Good release property
- Tracking profiles are possible
- HACCP-design
- Frayfree fabric
- FDA and EU compliant

#### Basic technical data

Top face	Silicone, smooth
Underside	Polyurethane impregnation
Article no.	906877
$d_{\min}$ [mm]	$r = 3 \text{ mm}$
Total thickness [mm]	1.1
$k_{1\%}$ relaxed [N/mm width]	4.0
Weight [kg/m <sup>2</sup> ]	1.1
Permitted operating temperature	-30 to +100 °C

Product Quick Info TR-906877-2 - 12/20  
FMS - Reproduction of text or parts thereof only  
with our approval.  
Modifications reserved.

Forbo Siegling GmbH  
Lilienthalstraße 6/8, D-30179 Hannover  
Telefon +49 511 67 04 0, Fax +49 511 67 04 305  
www.forbo-siegling.com, siegling@forbo.com