

Nuway DSDC product accreditation

Design	Colour name	DSDC Rating*	DSDC Comments*
Tuftiguard HD	Plain	X	Unsuitable due to aluminium scraper bar
	Classic	X	Unsuitable due to aluminium scraper bar
	Design (all 4 colourways)	Х	Unsuitable due to aluminium scraper bar
Connect	All 7 colourways	X	Unsuitable due to aluminium carrier
Grid	All 12 colourways	Х	Unsuitable due to aluminium carrier
Tuftiguard	Plain with anodised aluminium	X	Unsuitable due to unbuffed rubber/aluminium anodised scraper
	Plain with black anodised aluminium	X	Unsuitable using black anodised aluminium scraper bar
	Plain with bamboo	X	Unsuitable due to unbuffed rubber
	Classic with anodised aluminium	X	Unsuitable using anodised aluminium scraper bar
	Classic with black anodised aluminium	X	Unsuitable using black anodised aluminium scraper bar
	Classic with bamboo	1b	Suitable using buffed strip & bamboo scraper bar
	Design with anodised aluminium	X	Unsuitable using anodised aluminium scraper bar
	Design with black anodised aluminium	X	Unsuitable using black anodised aluminium scraper bar
	Design with bamboo & charcoal	X	
	Design with bamboo & Ocean	X	
	Design with bamboo & Willow	X	
	Design with bamboo & Scarlet	Х	
	Design with bamboo & buffed (classic)	1b	Suitable using buffed strip & bamboo scraper bar

Issue date: September 2020 creating better environments



Nuway

DSDC product accreditation

	2016-074 FORBO FLOORING		
UNIVERSITY of STIRLING	DSDC RATING KEY	CSCC Dementia Design	
	NOV-16	Accredited Product	
*RATING	*RATING DESCRIPTION		
Class 1a	Flooring within this rating is plain and can be used indiscriminately. That said, bear in mind the need to contrast flooring and walls, skirtings, doors/frames, furniture and sanitary ware.		
	Contrast is the key word. We recommend a minimum contrast of 30 units LRV (Light Reflectance Value) between the critical surfaces mentioned above.		
Class 1b	Flooring within this rating is semi-plain (minimal texture or fleck/pattern, wood effect with no knots) and in general, can be used throughout.		
	Natural patterns such as timber and stone may be used in most areas due to their familiarity but with a degree of caution.		
	Bear in mind minimum contrast of 30 units LRV (Light Reflectance Value) between the critical surfaces mentioned above.		
Class 2	Flooring within this rating has some pattern and needs to be used with caution. The natural patterns such as timber and stone in this range are more figured/patinated and although still familiar they need to be used with more caution than the above range.		
	Bear in mind minimum contrast of 30 units LRV (Light Reflectance Value) between the critical surfaces mentioned above.		

For an environment to be considered 'dementia-inclusive' or 'dementia-friendly', careful consideration must be given to the entire specification, not just the flooring.

As with many design features, individual needs and preferences should also be considered. What is fine for one person, may not be the case for another.

For more information and to download our 'Designing for dementia care' brochure visit **www.forbo-flooring.co.uk/care**

Issue date: September 2020 creating better environments