Tessera layout





PRODUCT INFORMATION



Tufted textile floor covering in tiles

Supply of a textile tufted floor covering made of 100% polyamide 6 fibers and mass dyed, in 50 x 50 cm leaded tiles of Tessera layout type.

It will combine a very good resistance to traffic (number of tuft of 193 060/m²) and an acoustic efficiency to the noise of shock declared $\Delta Lw = 27$ dB. Its mass tinted fibers will give it a better resistance in time.

It will be antistatic office and adapted for dissipative installation.

At the end of its life, Tessera layout will be 100% recoverable.

It will benefit from a 10-year warranty and can be extended up to 6 additional years (depending on the conditions of use of the manufacturer's Coral or Nuway cleaning mats.



Technical specifications	
Commercial name	Tessera layout
Total thickness	5,8 (± 10 %) mm
Total weight	3895 g/m ²
Impact sound reduction	$\Delta Lw = 27 dB$
Sound absorption	aw = 0,15
Reaction to fire	Bfl-s1* - 25/06951F/11/15 (BTTG)

Environmental datasheet

• FDES compliant with NF EN ISO 14025, NF EN 15804+A1 and its national complement NF EN 15804/CN and available on INIES.

- TVOC emission rate < 100 μg/m3, class A+ (best health labeling class).
- Product free of all restricted substances (formaldehyde, pen-tachlorophenol, heavy metals, CMR 1A and 1B); complies with the European REACH regulation**.
- GuT and BRE certified63% recycled content in relation to the total weight of the product

Designed and manufactured with guaranteed electricity from 100% renewable sources.