

LVT Luxury Vinyl Tiles - tackified loose lay

Tackified loose lay LVT 100% made in Europe and phthalate free.


With tackified installation and high quality dimensionally stable tiles and planks, the floor covering is available in a range of natural wood designs and a selection of concretes and modern stones designs.

This compact printed PVC floor covering has a 0.55 mm thick calendered wear layer. It is available in tiles of $50 \times 50 \times 100 \times 100$

The floor covering will offer a residual indentation of 0.11 mm, a dimensional stability \leq 0.05% and an impact sound reduction of 14 dB.

The PUR Pearl™ wear layer facilitates maintenance and avoid any surface metallisation or maintenance by spray method throughout the product's lifetime.

The product has a 7-year warranty (+6 years with installation of Forbo's Coral or Nuway entrance mats).



Technical specifications	
Commercial name	Allura flex 0.55
Total thickness	4 mm
Wearlayer	0,55 mm
Total weight	5 200 g/m ²
Impact sound reduction	$\Delta L_w = 14 dB$
Residual indentation	≤ 0,11 mm
Reaction to fire	B _{fl.} s1 - 89208753.01br (TÜV Rheinland)
Commercial /light industrial use	33 - 34

Environmental datasheet

- EPD is available in Forbo's website



- Phthalate free
- TVOC emission rate < 20 $\mu g/m^3$, class A+ (best class in health safety labelling)
- Made from 50 % of natural raw material and 18 % of recycled content in the backing.
- Free from all restricted substances (formaldehyde, pentachlorophenol, heavy metals, CMR 1A and 1B); compliant with European REACH regulation
- 100% recyclable