

1. Unique identification	Each package is labelled with a unique batch number that can be traced back to the specifications drafted for this adhesive.	
2. Designation	Forbo Eurocol Nederland 711 Uniflex; white humidity and frost-resistant powdered tile adhesive for natural stone and glass mosaic.	
3. Application	Suitable for white and light coloured natural stone, glass mosaic and marble on almost any surface, such as wood, existing tiling, granito and underfloor heating systems. Suitable for interior and exterior application.	
4. Name and contact address manufacturer	<i>Forbo Eurocol Nederland B.V.</i> <i>Industrieweg 1-2</i> <i>NL-1521 NA Wormerveer The Netherlands</i> <i>Tel. +31 75 6271600</i> <i>Email: info.eurocol@forbo.com</i>	
5. Name and contact address authorized	n/a	
6. System of assessment and verification of constancy of performance	3	
7. Activity of the notified certification body as required by the harmonized standard	The registered certifying body IKOB-BKB, identification no. 0957, performed the activities under system 3 and showed that the tile adhesive in question fulfils the initial type certification requirements described in Annex ZA of NEN-EN 12004:2007+A1:2012 and issued the certification of performance constancy and the conformity certificate.	
8. European Technical Assessment	n/a	
9. Declared performance	C2TE in accordance with NEN-EN 12004:2007+A1:2012; a flexible, cement-bound powdered tile adhesive with increased strength and extended open time.	
Essential characteristics	Performance	Test method
Initial adhesive strength	$\geq 1 \text{ N/mm}^2$	NEN-EN 1348:2008 §8.2
Adhesive strength after water exposure	$\geq 1 \text{ N/mm}^2$	NEN-EN 1348:2008 §8.3
Heat exposure	$\geq 1 \text{ N/mm}^2$	NEN-EN 1348:2008 §8.4
Adhesive strength after water exposure and freeze/thaw	$\geq 1 \text{ N/mm}^2$	NEN-EN 1348:2008 §8.5
Open time 20 minutes	$\geq 1 \text{ N/mm}^2$	NEN-EN 1346:2008
Material behaviour in case of fire	Class E	NEN-EN 13501-1:2007+A1:2009
Released dangerous substances	see MSDS	
Optional characteristics	Performance	Test method
Increased sagging resistance	$\leq 0.5 \text{ mm}$	NEN-EN 1308:2008
Extended open time 30 minutes	$\geq 0.5 \text{ N/mm}^2$	NEN-EN 1346:2008
Flexibility	S1 ($>2,5 \text{ mm}$ en $< 5 \text{ mm}$)	NEN-EN 12002:2008
Declaration drafted in accordance with Annex ZA of NEN-EN 12004:2007+A1:2012.		
10. The performance of the points 1 and 2 are consistent with the described product specified in paragraph 9 performance. This declaration of performance is issued under the sole responsibility of the in item listed manufacturer 4.		
		Wormerveer, 22-08-2013 signed: ing. T.W. Breeuwer; Manager R&D 