## nuway® tuftiguard

### TECHNICAL SPECIFICATIONS

#### **Tuftiguard plain**



Maximum length per module	2500mm (Bamboo 2400mm)																
Maximum width per module	750mm																
Maximum weight per module	23kg/m <sup>2</sup>																
Depth	12mm	12mm								17mm							
Scraper bar material	Silver, black, sand, bronze or gold anodised aluminium				Bamboo				Silver, black, sand, bronze or gold anodised aluminium				Bamboo				
Construction	Open		Closed		Open		Closed		Open		Closed		Open		Closed		
Number of wiper strips	1	2	1	2	1	2	1	2	1	2	1	2	1	2	1	2	
Total weight (kg/m²)	11	12	14	15	10	11	13	14	14	15	16	17	13	14	15	16	
Max static load (kg/cm²)	200				100				200		,	200					
Dynamic load (kg) 2 wheels 80mm, 20,000 passes	200	200				100				200				200			
Frames	A selection of recessed matwell frames are available																
Ramp frame model	ARF 50	ARF 50								ARF 70							
Manufacturing method	Entran	Entrance flooring system with scraper bars and rubber wiper strips															
Wiper designs	Plain, r	Plain, natural fibres, coloured fibres															
Wiper material	Rubbe	r															
Pile material	100%	Polyami	de BCF														



### **CONSIDERATIONS**

**Bamboo** is a natural product so there

or Anodised Aluminium.



# nuway® tuftiguard


## TECHNICAL SPECIFICATIONS



**Tuftiguard Classic and Design – dimensions** 

14mm

16mm



12mm single closed

All dimensions are approximate.

### Scraper bars



Aluminium (Universal)



Black Anodised Aluminium (Classic & Design)




Bamboo (Classic & Design)




Gold Anodised Aluminium (Classic & Design)



Sand Anodised Aluminium (Classic & Design)



12mm single open



17mm single open



For more detailed information on the dimensions of our Nuway Tuftiguard Entrance Systems, please visit **www.forbo-flooring.co.uk/downloads**, or contact our Entrance Flooring Systems Customer Service team on 01773 740 688.