
Euroclean Sport 897

Properties:

- highly durable
- elastic
- Anti-Slip fulfilling DIN 18032 for sports floors

Adhesive for:

- as initial care for suitable, water-resistant floor coverings e.g. sealed parquet, linoleum, PVC, ceramic (plastic coating coat for surface protection)
- refreshing old, water-resistant resilient floor coverings and old plastic coatings

Technical data:

Base:	Polyacrylate
Colour:	milky
Density:	approx. 1,02 g/cm ³
pH-value:	8,6
Processing temperature:	15 – 25 °C
Consumption:	1 l for approx. 25 - 30 m ² (1 coat)
Mode of application:	wiper mop or lint-free cloth
Cleaning agent:	water
	891 Euroclean Basic
Shelf-life:	min. 24 months at a frost-free and dry place (5 - 30°C), bottle to be closed air tight
Code acc. to GEV*:	no
Sensitive to frost	yes
GISCODE	GE20

Above mentioned data was made in laboratory. Due to a huge variety of different applications, these data should be considered as standard values only.

* International Hazardous Material Regulations

Instruction for use: The Eurocol 897 Euroclean Sport is to be applied with a wiper mop or lint-free cloth **undiluted** once or twice. Please apply 897 in one operation to avoid overlapping. For absorbent floors and floors with open pores, a few coats of 897 Euroclean Sport might be necessary to achieve the required finish. The drying time of each coat at normal room climate is 1 – 2 hours (ready for foot traffic) do not try to work on or walk on until fully dry. If heavy traffic is to be expected, approx. 12 hrs. drying time, overnight is recommended.

Refreshing old floors: Clean the floor with Eurocol 891 Euroclean Basic to remove all old cleaning agent residues. Afterwards please wipe the floor off twice with cold, fresh water. Before applying 897 Euroclean Sport, allow the floor to dry min. 12 – 24 hours.

Note: Eurocol 897 Euroclean Sport creates a skid-proof protection film on the floor which makes the floor dirt-repellent and tread-sure. This elastic basic protection is water-resistant and long-lasting.

Initial care of lacquered parquet can only be done once the lacquer is fully dry (3 - 10 days after final lacquer coat application depending on type of lacquer). Initial care of elastic floor coverings should be done prior to start of traffic.

For **regular cleaning**, we recommend water-soluble product like Forbo 896 Universal Maintenance Anti Slip

Old residues of Eurocol 897 Euroclean Sport are to be removed with Eurocol 891 Eurocare Basic (to be diluted with water approx. 1:3). According to the thickness of the old residues, Eurocol 891 Eurocare Basic might be applied once more.

Please pay attention to the technical information of auxiliary materials.

Tools need to be cleaned with water immediately after use.

Cleaning:

Relevant norms and regulations of the branch are to be respected. Outside Germany relevant national regulations are to be applied which must be known by the installer.

Packaging:

10 l packaging net, 60 buckets per pallet

Special note:

Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed.

This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work.

The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturers liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore, the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content.

As the usage, processing- and storage conditions on site are beyond the manufacturers influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to follow by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use. This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!

Technical information and Material Safety Data Sheets of concomitantly used installation materials must be followed carefully.

The products delivered by the manufacturer are for professional use only. Keep away from children.
The manufacturer's terms and conditions are binding.

TI_75227_897_EN

Last updated: 29. January 20118
Supersedes issue dd. 211 July 2012