



## Technical specifications

Surestep decibel meets the requirements of EN 13845 and EN 651

	Total thickness	EN-ISO 24346	3.0 mm
	Thickness wearlayer		0.7 mm
	Commercial use	EN-ISO 10874	34 very heavy
	Industrial use	EN-ISO 10874	42 general
	Roll width	EN-ISO 24341	2 / 4 m
	Roll length	EN-ISO 24341	± 25 m
	Total weight	EN-ISO 23997	2.8 kg/m <sup>2</sup>
	Acoustical impact noise reduction	EN ISO 171-2	17 dB
	In-room impact noise	NF S 31-074	Ln,e,w < 65 dB, Class A
	Dimensional stability	EN-ISO 23999	≤ 0.1 %
	Residual indentation	EN-ISO 24343-1	≤ 0.15 mm
	Abrasion resistance	EN 660-2	group T
	Castor chair continuous use	ISO 4918 / EN 425	no effect
	Light fastness	ISO 105-B02	≥ 6
	Flexibility	EN-ISO 24344	Ø 10 mm
	Resistance to chemicals	EN-ISO 26987	very good
	Slip resistance	DIN 51130	R10
		EN 13845 Annex C	ESf
		Pendulum test (wet) BS7976-2	≥ 36 Low slip risk
		Surface roughness	≥ 20 microns
	Electrical resistance	EN 1081 (R1)	> 1·10 <sup>9</sup> Ω
	Surface finish		PUR Pearl™
Surestep decibel meets the requirements of EN 14041			
	Reaction to fire	EN 13501-1	B <sub>f</sub> -s1
	Slip resistance	EN 13893	DS - μ ≥ 0.30
	Body voltage	EN 1815	≤ 2 kV
	Thermal conductivity	EN 12524	0.25 W/m·K



All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001. All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001. The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.