


Technical specifications


Nuway heavy duty & heavy duty FR

	Nuway heavy duty – plain, classic, design, select and FR (Note: FR is only available in a single colour option)	
Maximum length per module	2500mm	
Maximum width per module	750mm	
Maximum weight per module	23kg/m ²	
Depth	12mm	17mm
Scraper bar material	Aluminium	
Construction	Closed	Closed
Number of wiper strips	2	2
Total weight (kg/m ²)	17	24
Max static load (kg/cm ²)	900	
Dynamic load (kg) 2 wheels 80mm, 20,000 passes	350	
Fire behaviour EN13501-1	C _{fl} -s1 (with FR rubber)	B _{fl} -s1 (with FR rubber)
Ramp frame model	ARF 50	ARF 70
Manufacturing method	Entrance flooring system with scraper bars and rubber wiper strips	
Wiper designs	Plain, grey fibres, coloured fibres	
Wiper material	Rubber / FR Rubber	
Pile material	100% Polyamide BCF	

Nuway heavy duty plain




12mm Double closed




17mm Double closed

Nuway heavy duty design/select/FR



12mm Double closed



17mm Double closed

Considerations

PVC is temperature sensitive. When specifying entrance flooring for areas where temperature may increase significantly such as in glass atriums, beneath hot air blowers, in south facing areas or within heat 'curtains' please contact the support team on **01773 740 688** for advice.

In very brightly lit areas, the strong contrast between a light aluminium scraper bar and a dark wiper strip can sometimes create a strobe effect, which should be avoided. To prevent this type of occurrence, consider using a less contrasting colour combination of scraper bar and wiper strip from our wide range.



Nuway was the very first entrance matting brand to receive Building Research Establishment (BRE) certification and Forbo, at the time of press, is still the only manufacturer to offer BRE accredited products in this sector.