

Initial site clean

Remove all debris off the product and vacuum the surface to remove any fine particulate soiling.

Daily Cleaning

- Brush(optional) or vacuum to remove dry soiling
- Remove chewing gum and other sticky deposits
- Remove spots from Coral wiper strips with a neutral spot cleaner ensuring the area treated is thoroughly rinsed with clean water

Regular Maintenance Cleaning (Coral textile wiper strips)

- Repeat as above Daily Clean to ensure all dry particulate soiling and sticky residue are removed
- Clean matting to remove all residual soiling using one of the following methods:
 - Dry compound clean. This can be done manually with a brush or using a brush action machine. Ensure all powder residues are thoroughly removed by vacuuming
 - Counter rotating brush head machine using a neutral detergent suitable for polyamide fibres, ensuring all detergent residues are removed by rinsing thoroughly with water
 - A hot water extraction machine. Only use neutral detergents suitable for polyamide fibres, ensuring all detergent residues are removed by rinsing thoroughly with water

Note: hot water extraction cleaning can be carried out with the matting sections in situ provided the matting is not allowed to get saturated on the underside. Do not exceed 50°C temperature when using hot water systems.

Periodic Cleaning – mat and matwell

- Repeat as above Daily Clean to ensure all dry particulate soiling and sticky residue are removed from the surface of the matting
- Remove matting sections from the matwell taking care to note the position of each section for correct replacement. Clean residual soiling in matwell
- Clean Coral wiper strips to remove all compacted residual soiling using a hot water extraction machine. Only use neutral detergents suitable for polyamide fibres, ensuring all detergent residues are removed by rinsing thoroughly with water
Please refer to note above re water and temperature.
- Bristle and rubber wiper strips should be vacuumed and jet washed to remove residual soiling deposits.

General Tips

- An entrance system works more effectively when clean and free from residual soiling
 - Regular cleaning is more beneficial and cost effective than occasional heavy cleaning
 - Always follow Health and Safety Guidance particularly for lifting mat sections
 - Always follow the manufacturer's instructions for cleaning products
-
- Remember bold colours may need to be cleaned more frequently to retain their appearance and avoid tracking in walking areas

Protect newly laid flooring

All newly laid floors including entrance matting should be covered and protected from all other trades during building or remedial works with a suitable non-staining protective covering

Use recommended cleaning products

High quality cleaning products and equipment ensure efficient maintenance and represent only a small proportion of maintenance costs

Frequently asked questions

How often should I clean and maintain my mat?

A daily and regular cleaning regime should be in place to ensure the matting retains its performance.

The frequency of vacuuming and regular cleaning will depend upon the traffic volume and soiling type for each individual entrance

How do I remove chewing gum and soiling?

Chewing gum should be removed from Coral textile wiper strips using a proprietary product such as a gum remover gel. Other spots and spillages should respond to the methods mentioned above.

Can high alkaline cleaners or bleaching agents be used on wiper strips?

Only pH neutral cleaning products suitable for polyamide fibres should be used to clean the wiper strips.

Further help

Specialist matwell and matting cleaning contractors are available to undertake remedial cleaning.

Please contact Forbo Technical Service Department for further information.

Forbo Flooring UK Limited
PO Box 1
Kirkcaldy
KY1 2SB

www.forbo-flooring.co.uk
email: info.uk@forbo.com
Telephone: 0800 0282 162