

Technical specifications

Nuway Grid

| | 12mm Grid | | 17mm Grid | |
|--|--|---|--|---|
| Maximum length per module | 3000mm | | 3000mm | |
| Maximum width per module | 750mm | | 750mm | |
| Maximum weight per module | 23kg | | 23kg | |
| | Rubber | Textile | Rubber | Textile |
| Depth to height of aluminium | 12mm | 12mm | 17mm | 17mm |
| Depth to height of infill | 14mm | 18mm | 19mm | 23mm |
| Infill material | Rubber | Burford/Coral Classic/ Coral Brush pure | Rubber | Burford/Coral Classic/ Coral Brush pure |
| Construction | Closed | | Closed | |
| Total weight | 10.5kg/m ² | Approx 9kg/m ² | 17.2kg/m ² | Approx 15kg/m ² |
| Max static load | 100kg/m ² | | 100kg/m ² | |
| Dynamic load 2 wheels 80mm, 20,000 passes | 200kg | | 200kg | |
| Ramp frame model | ARF 50 | | ARF 70 | |
| Manufacturing method | Entrance flooring system with carriers and rubber infills | Entrance flooring system with carriers and textile infills | Entrance flooring system with carriers and rubber infills | Entrance flooring system with carriers and textile infills |
| Wiper material | Rubber | Needlefelt/PVC backed textile | Rubber | Needlefelt/PVC backed textile |
| Pile material | N/A | 100% polypropylene/100% polyamide BCF | N/A | 100% polypropylene/100% polyamide BCF |