









Technical specifications

	Total Thickness	EN-ISO 24346	6.0 mm
	Collection size		15
	Roll Width	EN-ISO 24341	1.22 m (3 colours in 1.83 m)
	Roll Length	EN-ISO 24341	≤ 28 m
	Total Weight	EN-ISO 23997	4.700 g/m ²
	Flexibility	EN-ISO 24344	Ø 50 mm
	Acoustical sound absorption	EN-ISO 354	0.10
	Self-healing properties	LH000420	yes
	Force on pins - Perpendicular to pin direct	LH000421	25 N (typical)
	Force on pins - Perpendicular to pin at 7 mm	LH000421	10 N (typical)
	Force on pins - Parallel to pin (pulling the pin out)	LH000421	15 N (typical)
	Bacteriostatic properties	EN-ISO 22196	Marmoleum has natural bacteriostatic properties which are confirmed by independent laboratories, even against the bacteria MRSA.
	Resistance to chemicals	EN-ISO 26987	Resistant to diluted acids, oils, fats and to the conventional solvents. Not resistant to prolonged exposure to alkalis.
	Anti-static		yes
	Gloss		Only available in matt colours: low reflection of sunlight or artificial light

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.
All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

