

FORBO FCT TECHNICAL DATA

1. PRODUCT NAME & MANUFACTURER

1.1 Product:

Forbo FCT (Flocked Carpet Tile)

1.2 Manufacturer:

Forbo Flooring Systems US
8 Maplewood Drive
Hazleton, PA 18202
1-800-842-7839

Forbo Flooring Systems Canada
3983 Nashua Drive, Unit 1
Mississauga, ON L4V 1P3
1-800-268-8108 (English)
1-800-567-9268 (French)

www.forboflooringNA.com

1.3 Product Description:

Construction: Forbo FCT is a flocked textile floor covering has 100% nylon type wear layer with an intermediate fiberglass layer, closed cell PVC foam layer and a recycled vinyl cushioned backing.

1.4 Physical Characteristics:

(dimensions are approximate)

Size ----- Approx. 19.69" x 19.69" (50 cm x 50 cm)

Gauge----- 0.19" (5.0 mm)

Packaging----- 19.69" x 19.69": 12 tiles (32.3 ft², 3 m²)

2. PRODUCT PERFORMANCE & TECHNICAL DATA

2.1 Environmental:

Compliant with CDPH 01350 requirements for VOC emissions and indoor air quality.

Forbo Flotex contributes to LEED v4.1 credits. For additional information, contact Forbo Flooring Systems.

2.2 Wear Layer Density:

Over 70,000,000 fibers per square meter.

2.3 Durability/Appearance Retention:

Wear Layer Composition is 6.6 nylon type. Class 4 (heavy duty) when tested in accordance to EN 1307, Classification of Pile Carpets (Wear Classification).

Achieves over 60,000 cycles when tested in accordance to the Wira Abrasion Test.

Achieves 95% recovery in 24 hours; 100% in one week when tested in accordance to ISO 3416-86, Determination of Thickness Loss after Prolonged Heavy Static Loading.

2.4 Castor Resistance:

Suitable for office chairs with castors when tested in accordance with ISO 4918, Castor Chair Test.

2.5 Slip Resistance:

Meets or exceeds the industry recommendation of >0.5 for flat surfaces when tested in accordance with ASTM D 2047, Standard Test Method for Static Coefficient of Friction. Suitable for use on flat or inclined surfaces.

2.6 Colorfastness:

No color change when tested in accordance with AATCC 107, Colorfastness to Water.

No color change when tested in accordance with AATCC 16, Colorfastness to Light (Option 3).

Very slight color change when tested in accordance with AATCC 165, Colorfastness to Crocking Wet & Dry.

2.7 Bounce Rebound:

99.7% average rebound when tested in accordance to ASTM F 2117, Standard Test Method for Vertical Rebound Characteristics of Sports Surface.

2.8 Hygienic:

Forbo Flocked Carpet Tile (FCT) is a supplement to and not a substitute for standard infection control practices and has been shown to reduce microbial contamination based on Independent Laboratory Testing.

2.9 Fire Testing:

Class 1 when tested in accordance with ASTM E 648/ NFPA 253, Standard Test Method for Critical Radiant Flux.

Meets 450 or less when tested in accordance with ASTM E 662/ NFPA 258, Standard Test Method for Smoke Density.

Passes when tested in accordance to ASTM D 2859, Standard Test Method for Ignition characteristics of Finished Textile Floor Coverings (Pill Test).

FSR – 170; SDC – 135 when tested in accordance to CAN/ULC S102.2, Standard Test Method for Flame Spread Rating and Smoke Development.

2.10 Electrostatic Propensity:

1.6 Kv when tested in accordance with AATCC 134, Electrostatic Propensity of Carpets.

2.11 Electrical Properties:

0.1 Kv when tested in accordance to ISO 6356, Assessment of Static Electrical Propensity.

>10⁹ ohms when tested in accordance to ISO 10965, Determination of Electrical Resistance.

3. INSTALLATION

3.1 Adhesive:

Use Forbo V 1190, Sustain 1195, FST 1299 or Forbo 660 adhesive.

3.2 Installation Guidelines:

Refer to Forbo's Installation Guidelines for complete installation recommendations.

4. WARRANTY

Limited 30-year warranty. For complete details, contact Forbo Flooring.

5. CARE & CLEANING

Refer to Forbo's Floor Care Guidelines for complete care recommendations.