## tessera<sup>®</sup> format

With a distinctive textured construction and a sophisticated colour palette of 12 contemporary and commercially attractive tonal shades, Format has taken low loop piles into a new dimension. This hardwearing heavy contract carpet tile manufactured using new high tech tufting machines combines rich texture with densely packed low loops for superior aesthetic appeal and real added value.


A universally attractive tile suitable for heavy traffic enviroments in all types of commercial premises, Format boasts a high castor chair

rating, making it an ideal and cost-effective solution for busy offices large and small. Manufactured from 80% solution dyed yarn, with enhanced resistence to fading over time or through intensive cleaning, Format is a particularly attractive proposition for areas prone to soiling. Carefully coordinated space dyed yarns provide a subtle flecked effect throughout the tile adding visual interest to the floorspace and enhancing its soil hiding properties.


AQUAFIL M



## tessera<sup>®</sup> format




614 | mocha choca





608 | blue monday





| tessera <sup>®</sup> format technical specifications |
|--|
|--|

| Lessel a form              | hat technical specification | ns   |
|----------------------------|-----------------------------|--|
| Description                |                             | Textured loop pile carpet tile                                     |
| Dimensions / tiles per box |                             | 50cm x 50cm / 20 tiles per bo                                      |
| Total thickness            |                             | 6,1mm <u>+</u> 10%   |
| Installation Method        |                             | Broadloom, <sup>1</sup> / <sub>4</sub> turn, or tessell            |
| Pile composition           |                             | 100% Aquafil polyamide   |
| Dye Method                 |                             | 80% solution dyed, 20% space                                       |
| Pile Weight                |                             | 525gsm <u>+</u> 10%  |
| Total weight               |                             | 4,140gsm <u>+</u> 10%  |
| Stitch density             | Tufts per m2                | 255,312 /m2 ± 10%  |
| Primary backing            |                             | Polyester  |
| Secondary backing          |                             | Modified bitumen & polyeste  |
| Application                | EN 1307                     | Class 33, suitable for any type                                    |
| Dimensional stability      | EN 986                      | <u>≤</u> 0.2 %   |
| Castor chair               | EN 985                      | Minimum R Value: $\geq$ 2.4  |
| Light fastness             | EN ISO 105-B02              | >5   |
| Impact sound reducti       | on ISO 140-8                | 25dB   |
| Electrical resistance      | EN 10965 & EN1815           | <1 x 10 <sup>9</sup> Ω: Static dissipative.                        |
| Environmental              |                             | Material used in the construct<br>levels. All Tessera carpet tiles |
| Guarantee                  |                             | Format is guaranteed for 10 ye recognised contractor and reg       |
| Format meets the req       | uirements of EN 14041       |  |
| Reaction to fire           | EN 13501-1                  | B <sub>fl</sub> s1   |
| Slip resistance            | EN 13893                    | DS: ≥ 0,30   |
|                            |                             |  |

Forbo Flooring reserves the right to improve the specification of its products without giving prior notice. Errors and omissions excepted.

9



615 | peanut shell



613 | chimney sweep



603 | stepping stone



604 | lead pipe



617 | china clay



616 | wind swept

Please note: Digital representation may vary from the actual product. Please order a sample to see the full effect

| хо  |
|---|
|   |
| lated $\begin{bmatrix} 1 & 1 & 1 & - \\ 1 & 1 & - 1 & - 1 \end{bmatrix}$  |
|   |
| ce dyed   |
|   |
|   |
|   |
|   |
| er fleece   |
| e of heavy contract application   |
|   |
|   |
|   |
|   |
| Body voltage < 2kV.   |
| ction of Tessera carpet tiles are chosen for their low volatile organic compound (VOC)<br>are manufactured using 100% green electricity.                                    |
| rears under heavy contract conditions provided that it has been professionally fitted by a gularly maintained in accordance with the Forbo requirements currently in force. |
|   |
|   |