















Technical specifications

Coral Logo meets the requirements of EN 1307

coral® logo

	Total thickness	ISO 1765	Approx 8 mm
	Wear classification	EN 1307	33, commercial heavy
	Colours		logo series 43xx
	Available sizes (all sizes are approx.)		Standard mat sizes (inc. edges) Special mat sizes
	Roll sizes with 2.5cm edge each side		55 x 90 cm
	Mat sizes with 2.5cm edge all sides		105 x 155 cm
			105 x 300 cm
			155 x 197 cm
			155 x 300 cm
			197 x 197 cm
			197 x 300 cm
	Suitability for castor chairs	EN 985	Castor chair continuous use r=2.5
	Colour fastness ratings:		
	Light	EN ISO 105/B02	7
	Water	EN ISO 105/X12	4.5
	Water	EN ISO 105/E01	4.5
	Manufacturing method/type		Tufted, 5/32" cut-pile
	Designs		Hi-definition custom print
	Pile material		100% polyamide
	Tuft base		Non-woven polyester
	Backing		EVERFORT® vinyl
	Total weight	ISO 8543	Approx 4000 gram/m ²
	Pile installation weight	ISO 8543	Approx 1200 gram/m ²
	Pile thickness	ISO 1766	Approx 5 mm
	Pile density	ISO 8543	0.186 gram/cm ³
	Number of tufts		Approx 91,500/m ²
	Comfort class	EN 1307	LC3
	All Coral products meet the requirements of EN 14041, excluding loose-laid mats and rugs		
	Fire behaviour	EN 13501-1	C _f s1
	Slip resistance	EN 13893	DS: ≥0.30
	Personal charging	ISO 6356	< 2 kV

Recommended adhesives: For the latest installation instructions and recommended adhesives please visit www.forbo-flooring.co.uk/installation

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.

Coral is manufactured in a facility certified to SA8000 and OHSAS 18001.



Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this specification are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, express or implied in respect of the information, content, materials or products displayed in this specification and does not represent that the information is accurate, complete or current.



For more information:

e: info.flooring.uk@forbo.com

t: **0800 121 4780**

w: forbo-flooring.co.uk/coral

Senast uppdaterad
2023.02.21



FLOORING SYSTEMS