













furniture linoleum

		desktop [®]	walton crocodiles	
	Total Thickness	EN 428	2.0 mm	2.5 mm
	Collection size		20	24
	Roll width	EN 426	1.83 m	2.00 m
	Roll length	EN 426	≤ 30 m	≤ 32 m
	Total weight	EN 430	2.1 kg/m ²	2.9 kg/m ²
	Indentation-residual	EN 433	< 0.20 mm	0.08 mm*
	Light fastness	ISO 105-B02	Method 3: blue scale minimum 6.	
	Gloss level	ISO 2813	< 5	8*
	Resistance to chemicals	EN 423	Resistant to diluted acids, oils, fats and to the conventional solvents such as alcohol, white spirit, etc. Not resistant to prolonged exposure to alkalis.	
	Flexibility	EN 435	ø 50 mm	
	Heat resistance	EN 433	70 ° C	
	Life Cycle Assessment		LCA is the foundation for securing the lowest environmental impact	

* Typical value

Desktop meets the requirements of EN 14041



	Body voltage	EN 1815	< 2 kV	< 2 kV
---	--------------	---------	--------	--------

The above information is subject to modifications for the benefit of further improvements.

Forbo Flooring
 't Hofveld 4
 1702 Groot-Bijgaarden
 Tel: +32 2 464 10 10
 Fax: +32 2 464 10 11
 info.belgium@forbo.com
 www.forbo-flooring.be