
Forbo Project vinyl

Conditions of storage and transportation

I. Storage

1. Conditions of storage of compact PVC sheet flooring:

- Store in original packaging, with the Forbo producer's indication,
- Store in roofed areas that are dry, ventilated and not exposed to sunlight. Floor/storage surfaces should be even and smooth, without sharp objects sticking out or edges that could damage the goods,
- Store in temperatures from +5°C to +25°C; short-term deviations from the recommended range of temperature are admissible, however not more than $\pm 10^{\circ}\text{C}$,
- Protect against smudging, moistening, mechanical and chemical damage,
- Store at some distance from heating units and lighting units compliant with the building provisions,
- Store vertically or horizontally at the amount of max. 3 layers.

Attention: non-compliance with the recommended temperatures and/or the number of layers of storage may affect some of the utility parameters of PVC sheet flooring and may result in durable deformation of rolls.

2. Conditions of storage of PVC welding rods:

- Store in original packaging, with the Forbo producer's indication,
- In closed dry spaces with temperature variations between +5°C to +25°C, and protected against direct exposure to sunlight,
- At the distance of at least 1 m from heating units,
- Protect against mechanical and chemical damage, moistening and smudging.

II. Transportation

1. Conditions of transportation of compact PVC sheet flooring:

- Loading and unloading should be done by means of properly chosen transportation equipment, making it impossible to damage the packaging and goods,
- Transport always in roofed vehicles, and in the original producer's packaging,
- Transport should be executed in such conditions where product is protected against soaking, smudging and mechanical and chemical damage and in compliance with the provisions on loading the trucks and trailers,

- It is allowed to transport goods in temperatures until a minimum of -5°C provided that additional protection of cargo is used to prevent displacement. And long-term exposure to cold is prevented as sheet flooring is sensitive to mechanical damages in these temperatures,
- Storage of goods during transportation should be in compliance with the requirements indicated in point I.1.

2. Conditions of transportation of PVC welding rods:

- Loading and unloading should be done by means of properly chosen transportation equipment making it impossible to damage the packaging and goods,
- Transport always in roofed vehicles, in compliance with the provisions on loading of trucks and trailers, and in the original producer's packaging,
- Place the goods in layers to protect against damage,
- It is impermissible to throw products or packaging during loading and unloading,
- The cargo should be protected against displacement, soaking, smudging and mechanical and chemical damages,
- The storage of goods during transportation should be in compliance with the requirements indicated in point I.2.