
























Technical specifications

Step meets the requirements of EN-ISO 10582

Onyx+ meets the requirements of EN 15102:2007+ A1:2011

step®

			Safestep Aqua	Surestep Laguna	Surestep Stat Barefoot	Onyx+ wall covering
	Total thickness	EN - ISO 24346	2.0 mm	2.0 mm	2.0 mm	0.92 mm
	Thickness wear layer	EN - ISO 24340	0.7 mm	0.7 mm	0.7 mm	0.1 mm
	Commercial: very heavy	EN - ISO 10874	Class 34	Class 34	Class 34	-
	Light industrial	EN - ISO 10874	Class 43	Class 43	Class 43	-
	Collection size		8	15	3	17
	Roll width	EN - ISO 24341	2.00 m	2.00 m	2.00 m	2.00 m
	Roll length	EN - ISO 24341	20 - 27 m	20 - 27 m	20 - 27 m	30 m
	Total weight	EN - ISO 23997	2.75 kg/m²	2.75 kg/m²	2.75 kg/m²	1.6 kg/m²
	Dimension stability	EN - ISO 23999	< 0.1%	< 0.1%	< 0.1%	-
	Residual indentation	EN - ISO 24343-1	≤ 0.05 mm	≤ 0.05 mm	≤ 0.05 mm	-
	Castor chair	EN 425	No effect	No effect	No effect	-
	Use in wet areas	EN 13553	Yes	No	Yes	Yes
	Light fastness	EN ISO 105 B-02	≥ 6	≥ 6	≥ 6	≥ 6
	Flexibility	EN - ISO 24344	ø 10 mm	ø 10 mm	ø 10 mm	-
	Slip resistance	AS/NZS 4586-2013 Oil/Wet Inclined Ramp	R10	R10	R10	-
		AS/NZS 4586-2013 Wet Pendulum	P3*	P3*	P3*	-
		AS/NZS 4586-2013 Wet Barefoot Ramp	Class C	Class B	Class B	-
	Chemical resistance	EN - ISO 26987	Very Good	Very Good	Very Good	Good
	Electrical resistance	EN 1081 (R1)	> 1.10 ⁹ Ω	> 1.10 ⁹ Ω	> 1.10 ⁹ Ω	-
	Creating better environments					
	Renewable electricity	Step is manufactured using 100% electricity from renewable sources				
	Recycled content	Step contains up to 70% recycled content in the backing				
Step meets the requirements of EN 14041						
	Reaction to fire	AS ISO 9239-1	CRF: 8.8kW/m² Smoke: 136%.min	CRF: 8.8kW/m² Smoke: 136%.min	CRF: 8.8kW/m² Smoke: 136%.min	AS 5637.1: Group 1
	Body voltage	EN 1815	< 2kV	< 2kV	< 2kV	-
	Thermal conductivity	EN 12524	0.25 W/m.K	0.25 W/m.K	0.25 W/m.K	-

* Disclaimer: Pendulum values of Forbo's safety vinyls have been achieved in an accredited 3rd party laboratory. Forbo will not be liable or responsible for highly variable and varying in situ results.

Recommended adhesives: For the latest installation instructions and recommended adhesives please visit www.forbo-flooring.com.au/installation

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPDs) which can be found on all of our websites. Step is manufactured in a facility certified to SA8000 and ISO 45001.



Whilst Forbo Flooring Systems Pty Ltd does its best to ensure that the contents of this specification are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring Systems Pty Ltd makes no, and expressly disclaims all, guarantees of any kind, expressed or implied in respect of the information, content, materials or products displayed in this specification and does not represent that the information is accurate, complete or current.



For more information:

✉ info.au@forbo.com

☎ 1800 224 471

🌐 forbo-flooring.com.au/step

📄 forbo-flooring.com.au/downloads