

Forbo Environmental Data Sheet

Product name	Tessera Struktur 2 Linear
Product description	Tessera Struktur 2 Linear is a subtly textured tonal stripe with robust and hard wearing flat woven appearance. Struktur 2 Linear complies with all requirements of EN 1307: Textile Floor Coverings - Classification of Pile Carpets.
Manufacturing location	Bamber Bridge, United Kingdom
Site accreditation	ISO14001, ISO 9001, ISO 45001, SA8000®



Our footprint - how it's made

Environmental data		Independent assessment and rating	
Total recycled content	6504	ISO 9001 Quality Management System	Poly Sold Sold Sold Sold Sold Sold Sold Sold
of product by weight	65%	ISO 14001 Environmental Management System	bgi 80 Nation Semental Rasspent
Post industrial recycled content	65%	ISO 45001 Occupational Health and Safety Management	SSI ISO 45001 Occupational Health and Safety Management CERTIFIED
% renewable electricity & biogas used	100%	Tessera is made in an SA8000® certified facility	SAL

Your footsteps - how it performs

Health and well being

Air quality	Gold
AgBB/DiBt	Pass
Impact sound reduction	17 dB

Installation

Recommended adhesives

Carpet tiles must be adhered using an all over tackifier adhesive system: Forbo Eurocol 542 Eurofix Tack Plus, a solvent free release system, is recommended. Where periphery tiles are not constrained by fixtures e.g. walls, edge strips etc, it is recommended that such tiles are adhered using a permanent adhesive; Forbo Eurocol 640 Eurostar Special, again a solvent free adhesive is recommended. Adhesives must be applied according to the manufacturer's instructions and it is essential that tackifier adhesives are allowed to dry to a tacky finish before laying the carpet tile. Failure to do so could result in a permanent non-release bond.

Where contribution to credits for BREEAM sections HEA2 and HEA9 are required then low emission adhesive Eurocol 542 tack plus should be used. If a permanent bond is required, please use Eurocol 640 Eurostar special.



creating better environments

Maintenance

Appropriate care and maintenance is essential to longevity and appearance retention and is necessary to maintain product warranties. Refer to the clean and care instructions available from Forbo Flooring Systems. All Tessera products are suitable for cleaning using the Dry Fusion technique. Dry Fusion uses 95% less water than the normal system of cleaning, produces no waste product, uses non-hazardous and biodegradable cleaning solutions and all packaging and materials within the Dry Fusion System can be recycled.

End of life

Products suitable for reuse, recycling, downcycling and waste to energy. Forbo Flooring Systems works with recycling companies to clean, reuse and recycle used carpet tiles in the UK.

Contribution to Green Building Schemes

Forbo design principles (Reduce, Recycle, Reuse, Renew)

Reduce	Investment in an extruder has reduced our bitumen usage by 50%.
Reuse	Yarn ends are rewound and used in the production of new Tessera Carpet tiles. All Tessera samples can be returned allowing them to be reused or recycled, reducing the need for virgin materials.
Recycle	Yarns, backing cloth, fillers and latex all contain recycled materials. All tufted Tessera carpet tiles contain at least 57% recycled content by weight.
Renew	All Tessera carpet tiles manufactured at Bamber Bridge are made with 100% renewable forms of energy (renewable electricity & biogas).