# Forbo Environmental Data Sheet

# Our footprint - how it's made

Environmental data		Independent assessment and rating		
Total recycled content of product by weight	65%	ISO 9001 Quality Management System	ISO 9001 Quality Management	
		ISO 14001 Environmental Management System	ISO 14001 Environmental Management	
Post industrial recycled content	65%	ISO 45001 Occupational Health and Safety Management	ISO 45001 Occupational Health and Safety Management CERTIFIED	
% renewable electricity & biogas used	100%	Tessera is made in an SA8000® certified facility		
Carbon footprint				
Estimated carbon footprint using data from Environmental product declaration according to ISO 14025	Cradle to gate (A1-A3)	7.06 kg CO <sub>2</sub> eq/m <sup>2</sup>		
	Use (1 year) (B2)	0.763 kg CO2 eq/m <sup>2</sup>		

# Your footsteps – how it performs

# Health and well being

Air quality	Indoor Air Comfort Gold	
Prodis-GUT	CBEA6AEE0	
Impact sound reduction	17 dB	
Installation		
Recommended adhesives	Carpet tiles must be adhered using an all over tackifier adhesive system: Forbo Eurocol 542 Eurofix Tack Plus, a solvent free release system, is recommended. Where periphery tiles are not constrained by	

ninenueu aunesives	Tack Plus, a solvent free release system, is recommended. Where periphery tiles are not constrained by fixtures e.g. walls, edge strips etc, it is recommended that such tiles are adhered using a permanent adhesive; Forbo Eurocol 640 Eurostar Special, again a solvent free adhesive is recommended. Adhesives must be applied according to the manufacturer's instructions and it is essential that tackifier adhesives are allowed to dry to a tacky finish before laying the carpet tile. Failure to do so could result in a permanent non-release bond.
	Where contribution to credits for BREEAM sections HEA2 and HEA9 are required then low emission adhesive Eurocol 542 tack plus should be used. If a permanent bond is required, please use Eurocol 640 Eurostar special.

## creating better environments



### Maintenance

Appropriate care and maintenance is essential to longevity and appearance retention and is necessary to maintain product warranties. Refer to the clean and care instructions available from Forbo Flooring Systems. All Tessera products are suitable for cleaning using the Dry Fusion technique. Dry Fusion uses 95% less water than the normal system of cleaning, produces no waste product, uses non-hazardous and biodegradable cleaning solutions and all packaging and materials within the Dry Fusion System can be recycled.

## End of life

Products suitable for reuse, recycling, downcycling and waste to energy. Forbo Flooring Systems works with recycling companies to clean, reuse and recycle used carpet tiles in the UK.

# **Contribution to Green Building Schemes**

### BREEAM 2018

Compliant through declaration number 4789471078.143.1 Valid until July 2025

### Ska scheme (RICS)

M12 soft floor covering criteria	(Ska Offices Vs 1.2 2013)	(Ska Retail Vs 1.0 2012)	(Ska Higher Education Vs 1.0 2016)
	Meets	Meets	Meets

#### LEED (version 4.1)

Potential direct or indirect contribution to following categories and credits:	Materials and Resources		
		Building product disclosure and optimisation - sourcing of raw materials - up to 1 point	
		Construction and demolition waste management up to 2 points	
	Indoor environmental quality	Low emitting materials up to 3 points	
		Acoustic performance up to 1 point	

#### Forbo design principles (Reduce, Recycle, Reuse, Renew)

Reduce	Investment in an extruder has reduced our bitumen usage by 50%.		
Reuse	Yarn ends are rewound and used in the production of new Tessera Carpet tiles. All Tessera samples can be returned allowing them to be reused or recycled, reducing the need for virgin materials.		
Recycle	Yarns, backing cloth, fillers and latex all contain recycled materials. All tufted Tessera carpet tiles contain at least 57% recycled content by weight.		
Renew	All Tessera carpet tiles manufactured at Bamber Bridge are made with 100% renewable forms of energy (renewable electricity & biogas).		

visit www.forbo-flooring.co.uk/downloads for more information