

# eurocol

# 044

the strong connection

14-7-2026



## EUROPRIMER MULTI

Universal primer to improve the adhesion of levelling compounds on all stone subfloors such as sand-cement screeds and anhydrite cast floors. Also suitable for smooth and sealed surfaces such as terrazzo, ceramic tiles, monolithic floors, etc. Also suitable for wooden floors, old, fixed, water-resistant adhesive residues, asphalt floors. Suitable for indoor and outdoor use. Thanks to EMICODE EC 1PLUS (very low emission) also suitable for BREEAM projects.

### PRODUCT TYPING

|             |                     |
|-------------|---------------------|
| Base        | Acrylic dispersion. |
| Color       | White.              |
| Consistency | Thin liquid.        |

- Very low emission
- EMICODE EC 1PLUS
- Universal application
- Favourable spreading capacity
- IMO certification required projects

### PROPERTIES

|                    |                                                                                                          |
|--------------------|----------------------------------------------------------------------------------------------------------|
| Classification     | Emicode EC 1PLUS tested conform EN 13999-2/4.                                                            |
| Consumption        | 50 - 75 g/m <sup>2</sup> on impervious subfloors.<br>100 - 200 g/m <sup>2</sup> on absorbent subfloors.* |
| Flammability       | Non-flammable.                                                                                           |
| Sensitive to frost | Good resistance after complete drying.                                                                   |
| Specific weight    | Approx. 1.01 kg/l.                                                                                       |

### APPLICATION

Primer for:

- improving the adhesion of levelling compounds and cement-based tile adhesives on all stony surfaces
- wooden floors
- old, fixed and water-resistant adhesive residues
- asphalt floors
- terrazzo
- outdoor application under normal circumstances
- ceramic tiles
- self-levelling anhydrite floors
- power-floated floors.

**044 EUROPRIMER MULTI**

## PROCESSING

|                         |                                                                                                                  |
|-------------------------|------------------------------------------------------------------------------------------------------------------|
| Storage                 | Store cool and free from frost.                                                                                  |
| Tools                   | Foam roller or lambswool roller.                                                                                 |
| Drying                  | ½ - 1 hour on impervious subfloors. 1 - 2 hours on stony absorbent subfloors. App. 6 hours on anhydrite floors.* |
| Shelf Life              | 12 months, in unopened packaging.                                                                                |
| Cleaner                 | Water.                                                                                                           |
| Application temperature |                                                                                                                  |

\* The stated values are laboratory values which, given the large variation in climatological conditions, subfloor compositions and layer thicknesses, are only guideline values.

### Substrate:

- The subfloor must have a good tensile and compression strength. The subfloor should also be smooth, clean, permanently dry and free from grease, dirt and dust, according to the requirements of BS 8203 or DIN 18 365.
- Adhesion-reducing layers, old material residues must be removed by suitable mechanical measures in accordance with the specifications of DIN 18365/DIN 18356.
- Old fixed floors, such as ceramic tiles, terrazzo, stone floors, must be thoroughly cleaned and sanded matt after drying.
- Not suitable for moisture sensitive subfloors such as chipboard and water-soluble adhesive residues.
- In advance always seek our technical data sheets. In doubt about the application ask for technical advice.

### Instruction manual:

- Shake the packaging well before use.
- On smooth and impervious surfaces apply 044 Europrimer Multi evenly with a foam roller. For absorbent subfloors use a lambswool roller.
- If required 044 Europrimer Multi can also be applied with a spray-gun.
- Do not walk on the floor during drying time.
- After drying the subfloor can be treated as required.
- Clean tools immediately after use with water.
- Remove fresh spots immediately with water.
- When applying a second coat or in combination with 026 Eurprimer multi, the 044 Europrimer Multi must be fully dried and walkable.

### Working conditions:


Intended surrounding temperature : 18 - 23 °C.

Material and subfloor temperature : min. 15° - max. 20 °C.

Relative humidity : 40 - 70%.

Contains methylchloroisothiazolinone and methylisothiazolinone (3:1). May produce an allergic reaction.

## QUALITY AND GUARANTEE



## ENVIRONMENT AND HEALTH

|                        |                                                                                                                                                                                                                                                                                       |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hazard Class           | None.                                                                                                                                                                                                                                                                                 |
| Safety and environment | Safety data sheets of Forbo Eurocol products according to EEG-guideline 91/155. Keep out of reach of children. Do not eat, drink or smoke while processing the product. Only give completely empty containers for recycling. Material residues can be disposed of as household waste. |
| MSDS                   | For extensive information about safety and environment we refer to our website <a href="http://www.eurocol.nl">www.eurocol.nl</a> .                                                                                                                                                   |

## ITEM DATA

### 044 EUROPRIMER MULTI

Forbo Eurocol Nederland B.V. | Industrieweg 1-2 | Postbus 130 | 1520 AC Wormerveer | Tel: +31 (0)75 627 16 00 | [info.eurocol@forbo.com](mailto:info.eurocol@forbo.com)  
Forbo Eurocol Deutschland GmbH | August-Röbling-Straße 2 | DE - 99091 Erfurt | PF 80 02 53 | Telefon: +49 361 730 41 0 | [info.eurocol.de@forbo.com](mailto:info.eurocol.de@forbo.com)

Eurocol is part of the Forbo Group



| Article | Definition       | Packaging                 | EAN-code        |
|---------|------------------|---------------------------|-----------------|
| 044     | Europrimer Multi | 10 kg jerry can           | 8 710345 044011 |
| 044     | Europrimer Multi | 1 kg bottle               | 8 710345 004428 |
| 044     | Europrimer Multi | Box of 12 bottles of 1 kg | 8 710345 004411 |



Package 1 kg



Package  
2,5 kg

Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed. This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work. The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturers liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content. As use, processing- and storage conditions on site are beyond manufacturers influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to be followed by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use.

This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!

#### 044 EUROPRIMER MULTI