

Forbo Environmental Data Sheet

Product name	Coral Brush sheet and tile
Product description	Coral Brush entrance systems are a textile floor covering complying with all the requirements of the EN 1307 Class 33 specification.
Manufacturing location	Krommenie, Holland
Site accreditation	ISO14001, ISO 9001, SA8000®



Our footprint – how it's made

Environmental data

Total recycled content of product by weight	23%
Post industrial recycled content	23%
Post consumer recycled content	0%
% renewable electricity used	100%

Independent assessment and rating

ISO 9001 Quality Management System



ISO 14001 Environmental Management System



Coral Brush is manufactured in a SA8000® certified facility



Your footsteps – how it performs

Health and well being

AgBB/DiBt	Pass
CHPS 01350	Coral products comply to 01350 Indoor Air Quality Standard
Phthalate	Phthalate free product

Installation

Recommended adhesives The recommended adhesive for the Coral sheet collections is Eurocol 540 Eurosafe Special or 640 Eurostar Special, for Coral tiles 542 Eurofix Tac Plus is recommended.

For the Coral installation guides visit [our website](#).

Maintenance

Coral entrance mats will, by their nature and location, be one of the most 'abused' of all floor coverings within a building. Thorough and regular cleaning is essential to ensure optimum performance and to extend the lifespan of the products. The frequency of cleaning is determined by the traffic volume and level of soiling.

End of life

Coral products can be recycled, downcycled or used to recover energy at the end of their life.

Contribution to Green Building Schemes

LEED (version 2.2)

Potential direct or indirect contribution to following categories and credits:

Materials and resources

Recycled content credit 4

Regional materials, credit 5

Indoor environmental quality

Indoor environmental quality – low emitting materials credit 4.3

Forbo design principles (Reduce, Recycle, Reuse, Renew)

Reduce 100% of the yarn in Coral Brush is Econyl regenerated yarn, reducing the need for virgin material.
Reduce energy consumption by closing down unused compressors

Reuse

Installing an effective entrance system can reduce cleaning time by up to 65%
Increase re-use of wastes by introducing more efficient waste separation methods

Recycle

Recycle sampling material through the Back to the Floor scheme. Any yarn waste is returned to the yarn supplier for recycling

Renew

100% of the electricity used is from a renewable source

Detailed environmental product declarations and full Life Cycle Analysis

visit www.forbo-flooring.nl/downloads for more information