

Forbo Environmental Data Sheet

Product name	Flotex Tile/Plank	
Product description	Flotex Tile is comprised of a polyamide 6.6 pile above a glass fibre reinforced recycled PVC backing. Flotex Tile complies with all requirements of EN1307: Textile Floor Coverings – Classification of Pile Carpets.	
Manufacturing locations	Ripley, United Kingdom Chateau Renault, France	
Site accreditation	reditation ISO14001, ISO 9001, ISO 45001, SA8000°	



Our footprint - how it's made

Environmental data		Independent assessment and rating	
Total recycled content of product by weight	up to 49%	ISO 9001 Quality Management System	ISO 9001
		ISO 14001 Environmental Management System	ISO 14001
Post industrial recycled content	up to 49%	OHSAS 18001 Occupational Health and Safety Management	CHSAC 8031 Provincing rate are failer throughout
Post consumer recycled content	0%	Flotex tiles and planks are made	
% renewable electricity used 100% in an SA8000° certified fa	in an SA8000® certified facility		
		British Allergy Foundation	A SEAL OF THE SEAL

Carbon footprint

Estimated carbon footprint using data from Environmental product	Raw materials and production	11.10 kg CO ₂ eq/m ²
declaration according to ISO 14025	Use (1 year)	0.316 kg CO ₂ eq/m ²

Your footsteps - how it performs

Health and well being

_		
Air quality	Approved by Allergy UK	
AgBB/ABG	Pass	
CHPS 01350	Flotex products comply to 01350 Indoor Air Quality Standard	
Impact sound reduction	19 dB	
Bacteriostatic properties	Flotex tile/plank meets the requirements of AATCC 174-1 and 174-2	
Installation		
Recommended adhesives	ended adhesives Forbo recommends the use of 542 Eurofix Tack Plus, a solvent free tackifier adhesive. If a permar bond is required, please use Eurocol 640 Eurostar special. For more information about adhesives and environmental impact please contact	

info.eurocol@forbo.com.



creating better environments

	Flotex releases twice as many allergens on vacuuming as standard carpet. Flotex can be cleaned using standard cleaning materials without the need for harmful chemicals. Flotex is waterproof and can be steam or mechanically cleaned.		
End of life			
	Can be downcycled or sent to waste to energy		
Contribution to Gree	n Building Schemes		
BREEAM-NL			
Potential direct or indirect contribution to following categories and credits:	New Building and Renovation	MAT01 Environmental impact of building materials MAT03 Responsible sourcing of building materials	
	In-Use	RSC11 Measures for future re-use of materials and waste RSC16 Circular origin of incoming products and materials	
LEED (version 4)			
Potential direct or indirect contribution to following categories and credits:	Materials and resources	Building product disclosure and optimisation	
		Building product disclosure and optimisation - sourcing of raw materials	
		Construction and demolition waste management	
	Indoor environmental quality	Low emitting materials	
		Acoustic performance	
Forbo design principles (Red	luce, Recycle, Reuse, Renew)		
Reduce	All Flotex samples can be returned allowing them to be reused or recycled, reducing the need for virgin material		
Reuse	Producing a Flotex tile backing made from re-used and pre consumer waste obtained via our Back to the Floor scheme. Waste comes from other production sites within Forbo, but also from outside Forbo to optimise waste streams from external textile flooring companies		
Recycle	Installation waste can be recycled in the our plant in Ripley, Derbyshire, back into Flotex products		
Renew	Flotex tiles are produced using 100% renewable electricity		