

Forbo Environmental Data Sheet

Product name	Tessera Layout and Outline/planks
Product description	Tessera Layout and Outline features a palette of solid colours (Layout) with co-ordinated stripes (Outline). Layout and Outline are manufactured with 100% solution dyed yarn for superior colour fastness. Layout and Outline comply with all requirements of EN1307: Textile Floor Coverings – Classification of Pile Carpets.
Manufacturing location	Bamber Bridge, United Kingdom
Site accreditation	ISO14001, ISO 9001, ISO 45001, SA8000®



Our footprint – how it's made

Environmental data

Total recycled content of product by weight 61%

Post industrial recycled content 61%

% renewable electricity & biogas used 100%

Independent assessment and rating

ISO 9001 Quality Management System



ISO 14001 Environmental Management System



ISO 45001 Occupational Health and Safety Management



Tessera is made in an SA8000® certified facility



Carbon footprint

Estimated carbon footprint using data from Environmental product declaration according to ISO 14025 Raw materials and production 11.3 kg CO₂ eq/m²

Use (1 year) 0.804 kg CO₂ eq/m²

Your footsteps – how it performs

Health and well being

Indoor Air quality AgBB/DiBt Gold Pass

Prodis-GUT 2C31F4FE

Impact sound reduction 27 dB

Installation

Recommended adhesives The recommended adhesive for the Tessera collections is Eurocol Eurocol 542 Eurofix Tack. More information about adhesives and environmental impact via info.eurocol@forbo.com.

For the Tessera installation guides visit [our website](#).

Maintenance

Appropriate care and maintenance is essential to longevity and appearance retention and is necessary to maintain product warranties. Refer to the clean and care instructions available from Forbo Flooring Systems.

End of life

Products suitable for reuse, recycling, downcycling and waste to energy.

Contribution to Green Building Schemes

BREEAM-NL

Potential direct or indirect contribution to following categories and credits:

New Building and Renovation MAT01 Environmental impact of building materials
MAT03 Responsible sourcing of building materials

In-Use RSC11 Measures for future re-use of materials and waste
RSC16 Circular origin of incoming products and materials

LEED (version 4)

Potential direct or indirect contribution to following categories and credits:

Materials and Resources

Building product disclosure and optimisation - sourcing of raw materials

Construction and demolition waste management

Indoor environmental quality

Low emitting materials

Acoustic performance

Forbo design principles (Reduce, Recycle, Reuse, Renew)

Reduce Investment in an extruder has reduced our bitumen usage by 50%.

Reuse Yarn ends are rewound and used in the production of new Tessera Carpet tiles. All Tessera samples can be returned allowing them to be reused or recycled, reducing the need for virgin materials.

Recycle Yarns, backing cloth, fillers and latex all contain recycled materials.
All tufted Tessera carpet tiles contain at least 57% recycled content by weight.

Renew All Tessera carpet tiles manufactured at Bamber Bridge are made with 100% renewable forms of energy (renewable electricity & biogas).

visit www.forbo.flooring.nl/downloads for more information