













Technical specifications

Westbond FR meets the requirements of EN 1307

	Total thickness		10mm ± 10%
	Wear classification	EN 1307	Class 33
	Dimensions		50cm x 50cm
	Minimum order quantity		Stocked range 3.5m ² (1 box). Custom colours 250m ²
	Colour fastness ratings:		
	Light	EN ISO 105-B02	> 4
	Seawater	BS EN ISO-E02	4-5
	Pile material		80% dyed British wool/10% polyamide/10% polyester
	Construction		Fusion bonded carpet tiles
	Tile backing		Flame retardant PVC
	Total weight	ISO 8543	3600 gsm ± 10%
	Pile thickness	ISO 1766	7.5mm + 0mm/-0.5mm
	Pile weight	ISO 8543	1500 gsm ± 10%
	Pile density	ISO 8543	0.168 grams per cm ³
	Impact sound insulation	ISO 10140-3	28 dB
	Dimensional stability	ISO 2551	< 0.2 %
	Comfort class	EN 1307	LC5
	Installation method		Monolithic, tessellated or quarter turn
Westbond FR fusion bonded carpet tiles meet the requirements of EN 14041			
	Slip resistance	EN 13893	DS
	Electrical resistance	EN 10965 & EN1815	1 x 10 ⁹ Ω: Static dissipative. Body voltage < 2.0 kV
	Reaction to Fire/Smoke/Toxicity	IMO FTP code 2010 part 2 & 5	Passes the standards set by the IMO fire test procedures for use in vessels at sea

Westbond FR is made to order.

IMO tested and approved adhesives can be recommended upon request.

Final production might vary within commercial tolerances from sample.

Manufacturing specifications subject to normal industry tolerances.

Forbo reserves the right to improve the specification of its products without giving prior notice.

Errors and omissions excepted.



0338/16 164.117/0338/WCL MED53106