(	CE	DECLARATION OF PERFORMANCE	FLOORING SYSTE
1.	Unique identification code of the product-type:		
	0200307-DoP-011		
2.	Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):		
	Sphera StarT (EN-ISO 10581)		
3.	Intended use or uses of the construction produ	uct, in accordance with the applicable harmonised technical specific	ation, as foreseen by the manufacturer:
	For use as floor covering in buildin	ngs (see EN 14041) according to the manufacturer's	s specifications.
4.	Name, registered trade name or registered tra	de mark and contact address of the manufacturer as required pursu	uant to Article 11(5):

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

Forbo Novilon B.V., De Holwert 12, 7741 KC Coevorden, The Netherlands

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: Name of the notified body, that issued a test report for initial type testing based on the sampling by the manufacturer.

> CRET (n°2401) 3 rue du Bois Vert BP 30 F-59531 Neuville-en-Ferrain

not applicable

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:


not applicable

Declared performance 9

9.	Declared performance			
	Essential characteristics	Performance	Harmonised technical specification	
	Reaction to fire	$\frac{\mathbf{G}}{\mathbf{B}_{\mathbf{f}_{1}}-\mathbf{S}\mathbf{I}} = \mathbf{C}\mathbf{S}$		
	Content of Pentachlorophenol	° DL PCP	EN 14041: 2004/AC:2006	
	Formaldehyd Emissions	<sup>®</sup> NA H <u>CHO</u>		
	Slip resistance	µ ≥ 0,30		
	Electrical behavior (dissipative)	NPD		
	Electrical behavior (conductive)	NPD		
	Electrical behavior (antistatic)	≤ 2.0 kV		
	Thermal conductivity [W/mK]	0.25 W/m.K		
	Water-tightness	Pass		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4 Signed for and on behalf of the manufacturer by: Signed for and on behalf of the manufacturer by:

Arthur Evers - Director Operations



2/