

Forbo Environmental Data Sheet

Product name	Marmoleum 2.5mm Sheet
Product description	Marmoleum is a linoleum floor covering complying with all the requirements of EN-ISO 24011: Specification for plain and decorative linoleum
Manufacturing location	Assendelft, Netherlands Kirkcaldy, United Kingdom
Site accreditation	ISO14001, ISO 9001, ISO 45001, SA8000®



Our footprint – how it's made

Environmental data

Total recycled content of product by weight 43%

Post industrial recycled content 43%

Post consumer recycled content 0%


% renewable electricity used 100%


Independent assessment and rating

Nordic Swan 

Allergy UK Seal of Approval 

ISO 9001 Quality Management System 

ISO 14001 Environmental Management System 

ISO 45001 Occupational Health and Safety Management 

Marmoleum is manufactured in a SA8000® certified facility 

Carbon footprint

Estimated carbon footprint using data from Environmental product declaration according to ISO 14025	Raw materials and production	-0.042 kg CO ₂ eq/m ²
	Use (1 year)	0.331 kg CO ₂ eq/m ²

Your footsteps – how it performs

Health and well being

AgBB/DiBT Pass

CHPS 01350 Marmoleum products comply to 01350 indoor air quality standard

Air quality Allergy UK Seal of Approval

Impact sound reduction ≤ 5 dB

Bacteriostatic properties Marmoleum has independent tests to prove that it inhibits bacteria such as MRSA, C Difficile, Norovirus, Acinetobacter baumannii

Installation

Recommended adhesives Forbo recommends the use of 414 Euroflex Lino Plus.
Where contribution to credits for BREEAM sections HEA2 and HEA9 are required then low emission adhesive Eurocol 611 Eurostar Lino plus should be used.

Installation off-cuts of Marmoleum can be collected via our **Back to the Floor** scheme and recycled back into Marmoleum at our plant in Scotland.

Maintenance

Topshield Pro Unique dual layer finish. Resistant to staining and scuffing so reducing the amount of cleaning required. Can be completely renovated, unlike PUR finishes.

End of life

Marmoleum can be recycled or composted.

Contribution to Green Building Schemes

BREEAM 2014

BREEAM ratings (generic)	Building Type				Retail (Durability)	Retail (Fashion)
Linoleum – Plain and decorative linoleum (EN548)	Office	Education	Healthcare	Homes		
	A	A+	A+	A	A+	A+

BREEAM 2018

BREEAM 2018 – compliant through EPD declaration number 12CA64879.101.1

Ska scheme (RICS)

M12 soft floor covering criteria	(Ska Offices Vs 1.2 2013) Meets	(Ska Retail Vs 1.0 2012) Meets	(Ska Higher Education Vs 1.0 2016) Meets
----------------------------------	------------------------------------	-----------------------------------	---

LEED (version 4)

Potential direct or indirect contribution to following categories and credits:	Materials and Resources	Building product disclosure and optimisation - EPD up to 2 points
		Building product disclosure and optimisation - sourcing of raw materials - up to 1 point
		Construction and demolition waste management up to 2 points
	Indoor environmental quality	Low emitting materials up to 3 points
		Acoustic performance up to 1 point

Forbo design principles (Reduce, Recycle, Reuse, Renew)

Reduce	Marmoleum's Topshield Pro finish significantly reduces cleaning and maintenance costs in life. Marmoleum is made from 97% natural raw materials.
Reuse	All Marmoleum site offcuts can be returned to Forbo for reprocessing using our Back to the Floor initiative. After Marmoleum's long life it can be incinerated for landfill and this reclaims more energy that is used in production. It is also biodegradable in a controlled environment.
Recycle	Packaging used to deliver raw materials is separated and recycled externally.
Renew	All Marmoleum is produced using 100% renewable electricity. Marmoleum contains 62% renewable materials.

Detailed environmental product declarations and full Life Cycle Analysis

visit www.forbo-flooring.co.uk/downloads for more information