







Technical specifications

Allura Flex" meets the requirements of EN ISO 11638.

			Allura Flex 1.00	Allura Flex*0.55
×	Total thickness	EN-ISO 24346	5 mm	4 mm
* ×	Wear layer thickness	EN-ISO 24340	1 mm	0.55 mm
	Collection size		79	54
ů,	Domestic use	EN-ISO 10874	Class 23	Class 23
ΪΪΪ̈́	Commercial use	EN-ISO 10874	Class 34	Class 33
<i>iii</i> i)	Light industrial use	EN-ISO 10874	Class 42	Class 42
K A	Squareness and straightness	EN-ISO 24342	< 400 mm < 0.25 mm / > 400 mm < 0.35 mm	< 400 mm < 0.25 mm / > 400 mm < 0.35 mm
ß	Total weight	ISO 23997	6300 g/m²	5100 g/m²
	Wearlayer binder content	EN-ISO 10582	Type 1	Type 1
	Castor chair continuous use	ISO 4918	Pass	Pass
T.	Slip resistance (ramp test)	DIN 51130	R10	R10
<u>e</u>	Acoustical impact noise reduction	EN-ISO 717-2	14 dB	14 dB
	Residual indentation Typical value	EN-ISO 24343-1	≤ 0.20 mm ~ <i>0.10 mm</i>	≤ 0.20 mm ~ <i>0.10 mm</i>
7	Colour fastness to light	EN ISO 105-B02 method 3	≥6	≥ 6
$\overleftarrow{*}\bigcirc$	Resistance to chemicals	EN-ISO 26987	Very good	Very good
к л И И	Dimension stability	EN-ISO 23999	≤ 0.05%	≤ 0.05%
	Indoor Air Emissions: TVOC after 28 days	EN 16516	≤ 0.02 mg/m³	$\leq 0.02 \text{ mg/m}^3$
LCA	Life Cycle Assessment		LCA is the foundation for securing the lowest environmental impact.	
	Creating better envi	ronments		
\prec	Renewable electricity		Allura is manufactured using 100% electricity from renewable sources.	
O	Recycled content (mass)		23%	20%
	Allura meets the requ of EN 14041:2004	irements	EN 14041:2004 C C 0200131-DoP-209	EN 14041:2004
B _H -s1	Reaction to fire	EN 13501-1	B _n -s1,L,CS	B _n -s1,L,CS
°9€9 ≥0,30	Slip resistance	EN 13893	µ ≥ 0.30	µ ≥ 0.30
⁶ λ ₂₃	Thermal conductivity	EN 12524	0.25 W/mK	0.25 W/mK
% 20 kV	Body voltage	EN 1815	≤ 2.0 kV	≤ 2.0 kV

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.



