



furniture linoleum

desktop

creating better environments

forbo
FLOORING SYSTEMS

SEE ME, FEEL ME, TOUCH ME

Elegant and natural

Forbo's Furniture Linoleum Desktop, is a natural surfacing material that delivers the finishing touch for all high end 3D furniture designs such as desks, chairs, stools, cabinets, doors and displays. The material is flexible and can be applied as a surface on all kinds of constructions. Furniture Linoleum is renowned for its elegance and durability, radiating high quality and finesse.

Warm and tactile character

Furniture Linoleum delivers a combination of a satin matt surface with a warm, fine texture creating interior furniture with a truly distinctive, genuinely individual look and feel that really is unlike any other surface material available. The natural character of Furniture Linoleum Desktop means that the material achieves a beautiful patina over time.

Colour is the new black

Whilst the colourways of charcoal black and dark anthracite grey will always remain classic favourites amongst designers, Forbo's new Furniture Linoleum Desktop collection now offers a range of contemporary and modern colours that complement current design trends and interior styling features.



Unique benefits for users

- tactile finish that is warm and comfortable
- matt surface
- natural material
- environmentally friendly choice
- no marks from fingerprints
- antistatic
- long lasting vibrant colourways
- pleasant to write on



Unique benefits for manufacturers

- flexible
- easy to apply
- suitable for many kinds of substrates
- processes like wood
- coatable
- manual and industrial installation possible

THE FINISHING TOUCH

Forbo's Furniture Linoleum is distinctive the way it looks as well as the way it feels. Desktop has an earthy, solid quality to it, yet it also 'gives' when you touch it. It looks matt and natural and feels warm to the touch. And it has one other unique feature: it doesn't show fingerprints.

Hygienic and antistatic by nature

The all-natural composition and Forbo's special surface finish ensure that Furniture Linoleum is naturally antistatic. This gives it a key practical advantage in comparison with other furniture finishes because the surface actively resists the build-up of static charges. This helps to prevent dust or dirt from sticking to it and helps to ensure that the material remains unblemished, hygienic and clean.

Easy to apply

Flexible, organic shapes can be created by Furniture Linoleum as the material is naturally flexible, which makes it perfect for all kinds of furniture and interior furnishing requirements. Furniture Linoleum is supplied in a roll format and can be applied horizontally or vertically, as well as to curved surfaces. The material is also versatile enough to allow edge covers to be made to create a perfect finish.

A High-performing natural winner

Furniture Linoleum Desktop is produced from a very finely ground linoleum granulate created from pure oxidised vegetable linseed oil and natural pine rosin, to which wood flour and colour pigments have been added. The Furniture Linoleum is created by a calendar process which rolls the material on to an impregnated paper backing. It is finished with a water-based, cross-linked acrylic finish that protects the surface while maintaining the flexibility and special touch of linoleum.



Explore pinboard linoleum - Bulletin Board

Another product in our range of linoleum surface materials is pinboard linoleum. This material offers a practical, simple solution to collect and exchange thoughts and ideas whenever people plan, create and meet. This all-natural material can be applied framed or mounted directly to the wall or on furniture. Its surface is tactile & colourful, creating a decorative element in your space. Find out more on the Forbo website www.forbo-flooring.co.uk/bulletinboard



Furniture Linoleum has a unique character, is flexible and supplied as a sheet on a roll. The material can be easily milled and shaped, in the same way as wood.

FEEL, TOUCH, LOVE

With our products we aim to create a better quality indoor environment, for people to live and work. In the case of furniture linoleum this is created through high quality furnishing that is natural, hygienic, low emitting and a pleasure to touch and use.



Furniture Linoleum 4155 | pewter (chair covering) + Marmoleum Solid 3706 | beton (floor covering)

SIMPLE ELEGANCE

furniture linoleum


A number of new fresh and stylish colours have been added to the classic colour range as have several warm hues and natural tones used in contemporary furniture, providing inspiration for a hospitality feel.



Furniture Linoleum 4154 | burgundy + 4174 | conifer + 4180 | aquavert + 4183 | pistachio + Marmoleum Solid 3363 | lilac (floor covering)



4157 | pearl NCS 1010 - Y10R LRV 67




4177 | vapour NCS 2005 - G10Y LRV 50



4180 | aquavert NCS 3020 - B40G LRV 35




4183 | pistachio NCS 2010 - G30Y LRV 47



4185 | powder NCS 1510 - Y60R LRV 54



4178 | iron NCS 8000 - N LRV 8



4176 | mushroom NCS 2002 - Y LRV 54



4132 | ash NCS 5502 - G LRV 23



4174 | conifer NCS 8010 - B90G LRV 7



4184 | olive NCS 5010 - G LRV 18



4154 | burgundy NCS 7010 - R10B LRV 7




Furniture Linoleum 4155 | pewter



4166 | charcoal NCS 8502 - B LRV 6



4175 | pebble NCS 3502 - Y LRV 35




4155 | pewter NCS 7005 - B20G LRV 12




Furniture Linoleum 4186 | orange blast + 4164 | salsa + 4185 | powder + Marmoleum Solid 3360 | vintage blue (floor covering)



4181 | midnight blue NCS 5040 - R90B LRV 9




4164 | salsa NCS 2570 - Y90R LRV 9



4023 | nero NCS 9000 - N LRV 5



4172 | mauve NCS 7005 - Y80R LRV 11



4179 | smokey blue NCS 7010 - R90B LRV 8



4182 | spring green NCS 1050 - G60Y LRV 47



4186 | orange blast NCS 1080 - Y70R LRV 22



MULTIPLE AWARDS


Forbo Furniture Linoleum is widely recognised for its exceptional combination of aesthetic and functional properties and holds numerous prestigious awards including the Red Dot design award, the award for Good Industrial Design and the Interzum Award.



Furniture Linoleum 4023 | nero +
Marmoleum Solid 171 | cement
(floor covering)

REFERENCES

Furniture Linoleum Desktop can be applied in numerous areas such as offices and similar work environments, kitchens, shops and hospitality and leisure centres.



Designer: Suzanne Zolatan Illes | Produced: Furn by Ox | Photography: Maibritt Høj Clausen



Gira | www.gira.de



Sabine T. Appel | www.vonappel.dk



Designer: Thor Høy | Produced & photography: Nicolaj Bo™ | thdesign.dk / nicolajbo.dk



Sabine T. Appel | www.vonappel.dk



Designer: Karsten Lauritsen | Produced: Zesinger Zoo | Photography: Tom Jersø | dzoo.dk



Möbeltischlerei Marko Wust | www.tischlereiwust.de | Photography: Daniel Hanke

AN EYE FOR DETAIL


Furniture Linoleum can be milled and shaped like wood and, for edge solutions, it can be combined with other materials (also see page 22)



Produktion: &SHUFL | Design: | &SHUFL | www.andshufl.com



Normann Copenhagen ApS | Designer: Simon Legald | www.normann-copenhagen.com



Faust Linoleum | www.faustlinoleum.de | Photography: Arne Hofmann, Haw-Lin, Michael Kastenbauer, Studio Muy



Faust Linoleum



Møbelsnedkeri Kjeldtoft* | Designer: Arkitekt MAA Rasmua Thrane, Wilhelmsen, Marxen og Bech-Jensen A/S | Photography: Lars Kiel




Faust Linoleum



Confect A/S, Ribu Inventarsnedkeri A/S | Confect.dk, ribu.dk



Garde Hvalsøe A/S | Design: Søren Hvalsøe Garde | Photography: Pernille Kaalund | www.gardehvalsoe.dk



Design and craftsmanship form the secret to success of this unique surfacing material.

Furniture Linoleum 4164 | salsa + 4185 | powder + 4181 | midnight blue + 4186 | orange blast + Marmoleum Solid 3360 | vintage blue (floor covering)

EASY APPLICATION

Furniture Linoleum can be applied easily on all common materials such as MDF, chipboard and Plywood as well as steel or composite materials.

Furniture Linoleum has a special matt appearance to prevent unpleasant light reflections. Generally, Furniture Linoleum does not require additional treatment but an additional coat may be applied if required (e.g., a UV-resistant PU coating), using a spray gun for even application.

Colour

As Furniture Linoleum is made from natural raw materials, different production runs may show slight colour variations. This is something to bear in mind when repeating an order.

Drying room film

During the last phase of the production process, a yellowish tint – known as drying room yellowing – may form on Furniture Linoleum, especially on lighter shades. This may be visible when unpacking a roll or reusing a roll after storage. This is an entirely normal and natural phenomenon of furniture linoleum and disappears soon after exposing the product to natural light.

Handling and transportation


Furniture Linoleum is well protected by robust packaging to prevent it from being damaged during transportation. Keeping rolls vertical during transportation will also help with this. When the linoleum is cut into sheets, the individual sheets should be lifted rather than pulled. It's also advisable to use pallets when transporting large numbers of sheets.

Storage

Store rolls vertically and sheets horizontally (flat). Do not let dirt get between sheets and avoid situations in which heavy and/or sharp objects may be placed on top of the stack. To ease installation, store the linoleum at room temperature.

Preparations for installation

Cut Furniture Linoleum approximately 1% oversized. Lay it flat and leave it (along with the adhesive and the carrier material) to acclimatise for approximately 24 hours at room temperature



Furniture Linoleum 4164 | salsa + 4185 | powder + Marmoleum Solid 3360 | vintage blue (floor covering)

Application

Furniture Linoleum should always be applied to a carrier material, e.g.: MDF, chipboard, multiplex or pressed composite plates. Whenever two different types of material are stuck together, tension develops between them. To alleviate this, it is often necessary to 'counter balance' the material. This also applies to linoleum when adhered to a carrier, especially loose panels. It is recommended to apply a material with the same technical properties to both sides of the carrier material.

Where larger surfaces are concerned, the following aspects are important:

1. Choice of carrier material
2. Thickness, symmetry and strength of carrier material
3. Choice of backing material used for counterbalancing
4. Correct acclimatisation of materials being used.

The best results are achieved when the same material is applied to both sides of the carrier material, at the same time and in the same direction. Furniture Linoleum is flexible and resilient, and (apart from acclimatisation) no preparation is required before installing it. To prevent any undesirable projections in its surface, ensure that the surface of the carrier material and of the reverse side of the material are clean. The carrier material should be free of any irregularities or contaminants that could interfere with the flat, smooth finish.

Adhesive

The adhesive used largely depends on the manner of installation and the intended use of the finished product. The carrier material also plays a role.

	Manual installation	Industrial installation
Flat surface	Acrylic adhesive	Polyvinyl acetate
Curved surface	Polyvinyl acetate (contact)	Polyvinyl acetate
Pressing	-	Polyvinyl acetate
Vacuum forming	-	Polyvinyl acetate



Furniture Linoleum 4184 | olive +
Marmoleum Solid 3353 | eggplant purple (floor covering)

Manual application on a flat surface

If a flat surface is to be covered entirely with Furniture Linoleum:

1. Stick the slightly oversized linoleum to the carrier material. To prevent undesirable grin showing through of lines from the adhesive spreader, apply the adhesive to the carrier with a high-pile roller.
2. Press the linoleum firmly into the adhesive with, for example, a hand roller.
3. Saw, mill, cut or plane the carrier material and the linoleum together into the desired shape after the adhesive has set. Always use sharp tools.
4. If required, apply an edge trim.

Manual application of a set in surface

When applied to desktops, etc., Furniture Linoleum can be countersunk. To do this, stick the linoleum to a sheet of MDF (approx. 6mm thick) and install this combination in the rebated desktop.

Manual application to a curved form

Before applying Furniture Linoleum to a curved form, bear in mind that:

- It is easier to bend linoleum lengthways than widthways.
- The minimum bending diameter is 5 cm for Desktop, if at all possible, bend the material lengthways.
- The curved surface of the carrier material must not contain any sharp edges.
- Porous carrier materials must be pre-treated with a primer.



The following is the recommended method for applying Furniture Linoleum into a curved form:

1. Apply contact adhesive to the carrier material.
2. When the adhesive on the carrier material is half set, apply adhesive to the linoleum.
3. When the adhesive on the linoleum is half set, press the linoleum onto the carrier material. Start pressing at the flat end of the surface and gradually work towards the curve.
4. Rub your hand over the surface to expel any air bubbles. Work a small section at a time to ensure that the linoleum is applied properly before sticking the next section.

Cover Furniture Linoleum with masking tape if the furniture edges are to be coated e.g. with lacquer. Remove the tape immediately after coating. If you sand the edges, avoid damaging the linoleum surface. Immediately remove any adhesive residues with water. After the adhesive has dried, remove any hard residues with white spirit, then immediately remove any residue of white spirit with water.

Industrial installation

No special equipment is required to install Furniture Linoleum. Machinery and tools suitable to install HPL may also be used for Furniture Linoleum.

When employing a press or stacking press, ensure that the surface of the press and of the linoleum are clean. Furniture Linoleum can be pressed cold or warm (maximum 70° C). The pressure will vary between 75 and 150 bars and the pressing time from 2 to 15 minutes, depending on the adhesive used.

To a certain extent, Furniture Linoleum can be stuck to a surface which is curved in more than one direction (e.g. the seat of a chair). Press the linoleum in a mould together with plywood and adhesive into the desired shape.

NB: It is always advisable to carry out trials prior to commencing actual production. After the Furniture Linoleum has been stuck to the carrier material, machine it to size.

Techniques such as sawing, milling, drilling, cutting and planing can be employed. Always use sharp tools.



HYGIENIC AND CLEAN

Cleaning after application

- Remove any residual adhesive, coating and/or stains with a clean, moist cloth and, if necessary, a pH-neutral cleansing agent (e.g. Forbo Cleaner).
- Use white spirit to remove dried adhesive, then immediately remove the white spirit with a clean dry cloth.

Regular cleaning

- Clean with a damp cloth. The use of a pH neutral detergent is optional.
- Remove stains immediately after spillage.

Occasional maintenance

- Apply a 5% solution of a pH-neutral detergent in water.
- Allow to soak for 10 minutes.
- Scrub the surface gently with a soft scrub brush.
- Remove dirty water.
- Rinse with clean water and allow surface to dry.
- Apply a thin maintenance film of undiluted Forbo Monel.
- Buff vigorously with a clean (new) cotton pad.


Preventive measures and stain removal

- Sharp items may cause scratches, use soft protection in case of doubt.
- Remove stains such as ink, coffee, tea, red wine immediately after spillage.
- To prevent stubborn stains from forming; use coasters under flowerpots, vases, cups etc.
- Desk Top: for stubborn stains such as ink and pencil, use a clean cloth and neutral cleaner.




Finishing off the edges

Any type of edge finish is possible with Furniture Linoleum. Stick the edging with an adhesive that is transparent when dry, and immediately remove any residue. Always protect the Furniture Linoleum surface.



The easiest way to finish off edges is to cut Furniture Linoleum off straight and to mill and varnish the edges of the carrier material (figure A). Bevel the edges a little. It is also possible to finish edges with, for example, strips of aluminium, wood or plastic, for example. (figures B and C). Figure D shows Furniture Linoleum applied to edges; to achieve a good result, however, this technique requires a certain degree of both experimentation and expertise.



As mentioned, it is possible to round off the edges with Furniture Linoleum (figure E). Always provide an additional 3-5 cm of linoleum at the underside of the edge to prevent it from coming loose due to bending stress.




This design solution, namely the combination of tapered surface and half-round wooden strip, illustrates the many possibilities offered by Furniture Linoleum (figure F).



Industrial rounding

In general, machinery used to bend HPL can also be used to bend Furniture Linoleum. The maximum temperature employed should not exceed 70°C.



3. Water-based, cross-linked finish
2. Linoleum
1. Paper

Technical specifications



	Total thickness	EN-ISO 24346	2.0 mm
	Roll width	EN-ISO 24341	1.83 m / 2.0 m - Nero only
	Roll length	EN-ISO 24341	≤ 30 m
	Collection size		21 colourways
	Weight	EN-ISO 23997	2.1 kg/m ²
	Indentation-residual	EN-ISO 24341-1	< 0.20 mm
	Light fastness	EN-ISO 105-B02	Method 3: blue scale minimum 6.
	Gloss level	ISO 2813	< 5
	Flexibility	EN-ISO 24344	ø 50 mm
	Resistance to chemicals	EN-ISO 26987	Resistant to diluted acids, oils, fats and to the conventional solvents. Not resistant to prolonged exposure to alkalis.
	Heat resistance		70 °C
	Body voltage	EN 1815	< 2 kV
	Creating better environments		
	Renewable Electricity		Furniture Linoleum is manufactured using 100% electricity made from renewable sources.
	Recycled Content		Furniture Linoleum contains 28% recycled content by weight
	Back to the Floor		Installation off-cuts can be collected and recycled via Back to the Floor
	LCA Life Cycle Assessment		LCA is the foundation for securing the lowest environmental impact.

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001. All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001. The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPDs) which can be found on all of our websites. Furniture Linoleum is manufactured in a facility certified to SA8000® and OHSAS 18001.



