## **MARINE** FLOOR COVERINGS



creating better environments



As our floors are part of the indoor environment in which people live, meet and work, it is our mission to design and offer products that contribute in a positive way to the health and comfort of the individual. "Committed to the health of one" introduces a focus in our commitment to sustainability that centres around all aspects that concern your health, well-being and comfort in relation to our products and services, today as well as for future generations.

### CONTENTS

- 4 Flotex FR
- 10 Coral Marine FR
- 14 Westbond FR
- 20 Contact us

### CREATING BETTER MARINE ENVIRONMENTS ACROSS THE WORLD

Forbo understands that material choice is one of the most critical aspects of designing marine transport interiors.

The material sets the tone for the overall look and feel of a vessel with many criteria influencing the specification including aesthetics, durability, maintenance and the requirement of IMO certification. Add to this other performance requirements such as slip resistance, sound absorption, comfort, anti-static properties, cleanability and green credentials and it becomes obvious why flooring choice is a complex one.

Forbo Flooring Systems manufactures the widest range of floor coverings in the market and offers a portfolio of IMO and non IMO certified products. Our Key Account Managers will help you, and provide all the expert advice you need when selecting flooring for your marine projects. In addition to our core collections, we also offer a custom design service to help you create flooring designs that perfectly match your interior requirements.

We understand that aesthetics and corporate branding are of high importance, and that functionality and durability play an important role in defining different floor covering requirements.

#### Need to reduce the costs of cleaning?

In all marine transport environments, having protective entrance systems such as Forbo's Coral Marine FR can help greatly. With a cut pile construction of 60% wool and 40% nylon, it stops up to 95% of walked in dirt and moisture, which significantly reduces cleaning costs and prolongs the lifetime of the interior floorcoverings. It also meets the IMO standards.

#### COMMITTED TO THE HEALTH OF ONE WWW.FORBO-FLOORING.COM/CHO

#### IMO certified products are:

- Flotex FR (a unique flocked floorcovering)
- Coral Marine FR (a textile entrance system and corridor floor covering)
- Westbond FR (fusion bonded carpet tiles)
- Forbo's own IMO certified primers and adhesives

#### Non IMO products include:

- •Linoleum (Marmoleum)
- Vinyl: Safety, Acoustic and LVT (Step, Sarlon Trafic, Allura)
- Carpet tiles (Tessera)
- Flocked (Flotex)
- Entrance systems (Coral, Nuway)

### **flotex**<sup>®</sup> FR

Flotex FR is unique, combining the cleaning properties and durablity of a resilient flooring with the comfort, slip resistance and acoustic properties usually associated with textiles.

#### **Benefits:**

- Fully compliant to IMO Marine standards
- Smooth textile velour like surface that's comfortable and warm underfoot
- Excellent slip resistance
- 100% waterproof. Impervious backing makes it suitable for wet cleaning
- Durable construction: using Nylon 6.6
- Easy to clean
- Improved indoor air quality (independently proven by Allergy UK)
- Easy to repair any damaged areas
- Anti-microbial
- Flotex is phthalate free
- Excellent acoustic properties up to 22 dB
- Choose from an extensive range of designs and colours or use our custom design service
- High definition print offers you complete freedom of design.

PHTHALATE



## **flotex**<sup>®</sup> FR

THE ONLY **IMO CERTIFIED, WASHABLE,** TEXTILE FLOOR COVERING

Flotex FR is extremely dimensionally stable and has a velour-like surface whilst being functional and extremely easy to clean.

Having been awarded the prestigious Allergy UK Seal of Approval, Flotex FR is proven to offer consistent protection against bacteria and reduce allergens, improving indoor air quality for passengers.

Flotex FR can be digitally printed. Its high definition quality and specialist printing technology allow for large endless pattern repeats and vivid lifelike colours. This creates a new dimension for Flotex FR and provides ultimate design flexibility for marine environments.





IMO Certificate No. 164.117/1121/WCL MED0364

## flotex<sup>®</sup> vision FR


Flotex Vision FR offers an infinite number of design options ranging from abstracts with an intricate colour spectrum to realistic images of natural materials.

With over 500 items to choose from, Flotex Vision is best viewed on Forbo's online digital library which is continuously updated. The designs in Flotex Vision FR fall into six broad categories, each of which represents a different design direction: Floral, Lines, Shape, Pattern, Image and Naturals.



#### Lines

Line or stripe designs, each with their own characteristics, ranging from muted and sophisticated colourways to very complex and multi-colour patterns.



### Pattern

**Naturals** 

Textured, non-directional visuals created through the intricate interplay of networks and patterns.



**Floral** A selection of floral designs, ranging from abstract, graphic flower motifs to romantic images of roses and butterflies.



### Shape

A collection of organic shapes and motifs delivering beautiful all-over patterns, including both contemporary and traditional designs.



This collection offers photorealistic images of natural materials such as wood, stone, ceramics and cork floors. The design technology creates amazingly realistic aesthetics, with the added benefits of improved acoustics, slip resistance and reduced maintenance costs.



### Image

A design category containing a wide variety of photographic images. Grass, sand, water drops, buttons and street maps are just some of the possibilities to be found within this intriguing range.

### TOTAL DESIGN FREEDOM

Flotex Vision FR is a collection of high definition digital print designs that create superior textures with almost 3D like appearance. As Flotex Vision FR has 70 million fibres per square per metre, it provides a matt high density substrate for printing, enabling vibrant designs and true-to-life visuals to be produced in high level photographic resolution, providing ultimate design flexibility for marine interiors. All colours, tones and hues are achievable with Flotex Vision FR.




All of the Flotex Vision designs offer the option to create your own colourway, allowing you to match the floor precisely to your interior design scheme or corporate identity colours. If you have your own vision of what you want on the floor, we also offer a complete custom design service on request.





### www.flotexvision.com



## flotex<sup>®</sup> colour FR

Flotex Colour is a collection of three designs (Metro, Penang and Calgary) which together form a rhapsody of colour across a broad spectrum.

246008 | Metro anthracite

The swatches shown are only a small selection of the colourways available. Please refer to the Forbo Flooring website in order to see the full colour palette.

### flotex<sup>®</sup> colour FR

metro



# penang

482006 | Penang sage 482015 | Penang beige 482024 | Penang purple

**flotex**<sup>®</sup> colour FR



482023 | Penang dusk





## 290024 | Calgary fire 290009 | Calgary moss

290011 | Calgary quartz



290022 | Calgary condor

flotex<sup>®</sup> colour FR

calgary

290021 | Calgary aqua

290023 | Calgary expresso

#### **Technical specifications**

Flotex FR meets the requirements of EN 1307

	Total thickness	ISO 1765	Approx. 3.3 mm		
	Wear classification	EN 1307	Class 33		
2	Roll width		200 cm		
)	Roll length		30 m		
	Suitability for castor chairs	EN 985	Castor chair continuous use		
	Colour fastness ratings:				
	Light	EN ISO 105/B02	6		
	Rubbing	EN ISO 105/X12	≥ 4		
	Water	EN ISO 105/E01	≥ 4		
	Pile material		100% polyamide		
	Construction		Flocked textile floor covering		
	Backing		Resilient waterproof backing		
	Total weight	ISO 8543	Approx. 1225 gram/m <sup>2</sup>		
	Pile thickness	ISO 1766	Approx. 2 mm		
	Pile installation weight	ISO 8543	Approx. 250 gram/m <sup>2</sup>		
	Impact sound insulation	EN ISO 717-2	$\Delta$ Lw = approx. 22 dB		
	Dimensional stability	ISO 2551	≤ 0.20%		
	Flexibility	ISO 24344	No cracking (10 mm diameter Mandrel)		
	Electrical resistance	ISO 10965	Approx. 10°Ω		
	Comfort class	EN 1307	LC1		
	Flotex FR product meets the demands set by E	N 14041			
	Slip resistance	EN 13893	> 0.30		
	Body voltage	ISO 6356	< 2.0 kV		
	Fire rating:				
	IMO Resolution A653(16)		Pass		
	IMO Resolution MSC 307(88) Annex 1 Part 2		Pass		
	IMO Resolution MSC 307(88) Annex 1 Part 5		Pass		
	US Coast Guard approval ref: 164.117/1121/WG	CL	MED0364		
	Flotex FR is made to order. IMO certified adhesives can be recommended u Final production might vary within commercial tolerar Manufacturing specifications subject to normal indust Forbo reserves the right to improve the specification of it Errors and omissions excepted.	nces from sample. ry tolerances.	WO Certificate No. 164.117/1121/WO		

246001 | Metro indigo

### **TECHNICAL** SPECIFICATIONS







## **coral**<sup>®</sup> marine FR

Coral is the market leader in entrance systems providing an exceptionally versatile and proven range of 'clean-off' entrance system products and customisable carpets.

#### **Benefits:**

- Fully compliant to IMO Marine standards
- Stops up to 95% of walked in dirt and moisture
- High moisture absorption
- Excellent dirt storage/soil hiding
- Durable construction: using a 60% wool/40% nylon mix
- PVC and phthalate free
- Advanced colouring and choice
- All references stocked for quick delivery
- Using Coral Marine FR can reduce cleaning costs and prolong the lifetime of on board floor finishes and coverings.


# coral<sup>®</sup> marine FR

**TEXTILE ENTRANCE** AND **CORRIDOR** FLOOR COVERINGS

Coral Marine FR is a cut pile floor covering consisting of 60% wool and 40% nylon. It is the ideal choice for an entrance system, simultaneously absorbing moisture and removing dry soiling. Coral entrance systems can reduce cleaning costs and prolong the life of on-board floor finishes and coverings.

Coral Marine FR meets all the fire safety standards set by the International Maritime Organization (IMO) for products used in seagoing vessels. Yarn and backing systems have been developed to meet the stringent smoke toxicity and low flame spread standards required to achieve the IMO 'Wheelmark'.


confidence in cruise liners, passenger ferries, charter boats and other seagoing vessels, in addition to offshore facilities where the 'Wheelmark' classification is required.




As a result Coral Marine FR can be used with



IMO Certificate No. 164.117EC0493/MED0493/17









4226 | Tangier brown



4222 | Sidney blue

#### **Technical specifications**

	Total thickness	ISO 1765
	Area of use	
	Roll width	
	Roll length	
	Colour fastness ratings:	
R	Light	EN ISO 105/B02
	Rubbing	EN ISO 105/X12
	Water	EN ISO 105/E01
	Seawater	EN ISO 105/E02
	Shampoo	BS 1006
	Organic solvents	EN ISO 105/X05
	Construction	
	Designs	
	Pile material	
	Tuft base	
	Backing	
2	Total weight	ISO 8543
	Pile installation weight	ISO 8543
	Pile thickness	ISO 1766
	Pile density	ISO 8543
	Number of tufts	ISO 1763
	Impact noise reduction	EN ISO 717-2
(v))	Sound absorption	EN ISO 354:2003
P A pl DS	Slip resistance	EN 13893
Ţ.	Body voltage	ISO 6356
▤	Thermal resistance	ISO 8302
	Fire rating:	
	IMO Resolution A653(16)	
	IMO Resolution MSC 307(88) Annex 1 Parts 2 ar	nd 5
	US Coast Guard approval ref: 164.117EC0493	
	IMO certified adhesives can be recommended upon req	uest.

Final production might vary within commercial tolerances from sample. Manufacturing specifications subject to normal industry tolerances. Forbo reserves the right to improve the specification of its products without giving prior notice. Errors and omissions excepted.

4223 | Hong Kong red

### **TECHNICAL** SPECIFICATIONS

Approx. 9 mm							
Heavy use							
185 cm							
Roll len	gth appro	ox 27.5 m	(customi:	sable)			
>5							
4							
4-5							
4							
4-5							
5							
Tufted,	5/32" cut	-pile					
Mottleo	ł						
60% Wa	ool / 40%	polyami	de				
Non-wo	oven poly	yester					
FR latex	(						
Approx	. 2550 gr	am/m²					
 Approx	. 1120 gr	am/m²					
Approx	. 6 mm						
 0.141 g	ram/cm <sup>3</sup>						
 Approx	. 96,400/	m²					
Δ Lw 31	dB						
f(Hz):	125	250	500	1000	2000	4000	
ap:	0.05	0.05	0.1	0.3	0.55	0.6	
DS							
< 2.0 k\	/ antistat	ic					
0.125 m	n² K/W						
Pass							
Pass							
 EC0493	8/17						
				A			



O Certificate No. 164.117EC0493/MED0493/17

## westbond<sup>®</sup> FR

The Westbond wool carpet tile range is synonymous with sophistication and offers great warmth, comfort and acoustic benefits. Westbond FR carpet tiles are IMO certified and are ideally suited to many environments including cabins, restaurants, offices and lounge areas.

#### **Benefits:**

- Fully compliant with IMO Marine standards
- 50cm x 50cm tile format for easy installation and replacement
- Design flexibility to suit all interior design schemes available in 144 colours
- Create a unique look and feel with custom colours and designs
- Offers warmth and underfoot comfort.

# westbond<sup>®</sup> FR

INFINITE POSSIBILITIES AND EXCEPTIONAL QUALITY


> Fusion bonding is a sophisticated method of carpet tile manufacture where individual yarn pile is bonded onto the backing material to make an extremely dense and luxurious carpet tile. Each tuft is individual and a high proportion of the yarn is in the wear surface providing a beautiful, rich, velour carpet tile which gives an excellent broadloom appearance.

### Choose your own colours and combine them into a truly unique floor

Westbond allows customers to take control of the process of designing luxurious, custom carpet tiles with a heavy pile weight for the most prestigious installations.

Create your own carpet tile with a flex combination. The Flex carpet tile is unique to Westbond and offers the ideal solution for those seeking an individual look to the floor. Simply create your own carpet tile design by selecting colours from the Westbond FR range in a flex combination.

The results of your creativity can be easily and quickly realised with a sample to show you what the finished product will look like, dispatched within 24 hours.





IMO Certificate No. 164.117/EC0338/53106

### westbond<sup>®</sup> FR

Westbond is available in 144 colours that can be flexed together to create unique designs.



We offer 10 stocked designs, marked below with an asterisk. Below is only a selection of the colours available, for further information on the full range, please contact us.



\*Stocked items.
















W15579FR | ocean




W15585FR | crystal




W15421FR | bluebird\*



WF1521567FR | deep pacific\*



WF1521566FR | sea mist\*



WF1521565FR | night sky\*



WF1521568FR | high tide\*

### westbond<sup>®</sup> flex


Westbond Flex carpet tiles are the ideal solution for those seeking a truly individual look to the floor. By mixing shades from the Westbond Colour collection, or from a custom colour of your choice, you can simply create your own custom designed Westbond Flex carpet tile.

Within two working days we will send you a 'POM' that offers a realistic impression of what the finished carpet tile will look like.



### HOW TO CREATE YOUR UNIQUE WESTBOND FLEX DESIGN







Shown above are three plain yarns, which are combined together to create a chosen Flex design. A 'pom' is then created to help you visualise your unique finished carpet tile.

Total thickness	
Wear classification	EN 1307
Dimensions	
Minimum order quantity	
Colour fastness ratings:	
Light	EN ISO 105-B0
Seawater	BS EN ISO-E02
Pile material	
Construction	
Tile backing	
Total weight	ISO 8543
Pile thickness	ISO 1766
Pile weight	ISO 8543
Pile density	ISO 8543
Impact sound insulation	ISO 10140-3
Dimensional stability	ISO 2551
Comfort class	EN 1307

SC AND	Slip resistance	EN 13893
Ą	Electrical resistance	EN 10965 & EN1815
	Reaction to Fire/Smoke/Toxicity	IMO FTP code 2010 part 2 & 5

Westbond FR is made to order. Stocked items are shown on pages 16 and 12 IMO certified adhesives can be recommended upon request.

Final production might vary within commercial tolerances from sample. Manufacturing specifications subject to normal industry tolerances. Forbo reserves the right to improve the specification of its products without giving prior notice. Errors and omissions excepted.

### **TECHNICAL** SPECIFICATIONS

	10mm ± 10%
	Class 33
	50cm x 50cm
	Stocked range 3.5m <sup>2</sup> (1 box). Custom colours 250m <sup>2</sup>
	>4
	4-5
	80% dyed British wool/10% polyamide/10% polyester
	Fusion bonded carpet tiles
	Flame retardant PVC
	3600 gsm ± 10%
	7.5mm + 0mm/-0.5mm
	1500 gsm ± 10%
	0.168 grams per cm <sup>3</sup>
	28 dB
	< 0.2 %
	LC5
	Monolithic, tessellated or quarter turn
404	11
	DS
	1 x 10 <sup>9</sup> $\Omega$ : Static dissipative. Body voltage < 2.0 kV
	Passes the standards set by the IMO fire test procedures for use in vessels at sea
7.	Lloyd's Register

IMO Certificate No. 164.117/EC0338/53106

Forbo Flooring Systems is part of the Forbo Group, a global leader in flooring and movement systems, and offers a full range of flooring products for commercial and affordable housing and new build markets. High quality linoleum, vinyl, textile, flocked and entrance flooring products combine functionality, colour and design, offering total flooring solutions for any environment.



#### What to do now?

For more information about any of the products and services offered by Forbo Flooring Systems, to request samples/brochures or a visit then contact us:

Email: transport@forbo.com Website: www.forbo-flooring.com/transport Tel: +44 (0)1773 744121

#### Let us keep you up-to-date

Visit us at transport-flooring.com for more information.

Linkedin: Forbo Flooring Transport



### **TRANS**PRESS

Email us at **transport@forbo.com** to sign up to our quarterly transport newsletter for: - **Product information** 

- Design inspiration
- Forbo transport news
- Industry news

032018

#### All countries

Forbo Flooring UK Limited High Holborn Road Ripley Derbyshire DE5 3NT UK Tel: +44 (0) 1773 744121 Fax: +44 (0) 1773 744142 E-mail: transport@forbo.com www.forbo-flooring.com/transport



#### USA

Forbo Flooring NA Humboldt Industrial Park 8 Maplewood Drive PO Box 667 Hazleton, PA 18202 USA Tel: +570 450 0220

Fax: +570 450 0220 Fax: +570 401 7378 E-mail: info.na@forbo.com www.forboflooring.na@forbo.com

