













## Technical specifications

Flotex meets the requirements of EN 1307

## Flotex FR

## Flotex vision FR

	Total thickness	EN -ISO 24346 / ISO 1765	3.3 mm
	Roll width	EN-ISO 24341	200 cm
	Roll length	EN-ISO 24341	30 m
	Minimum order quantity		200 m <sup>2</sup> / 1000 m <sup>2</sup> (HD)
	Total weight	EN -ISO 23997 / ISO 8543	1225 gram/m <sup>2</sup>
	Pile installation weight	ISO 8543	250 gram/m <sup>2</sup>
	Pile thickness	ISO 1766	Approx 2 mm
	Pile material		100% polyamide
	Dimensional stability	ISO 2551	≤ 0.20%
	Light fastness	EN ISO 105/B02	≥ 6
	Electrical resistance	ISO 10965	≥ 10 <sup>9</sup> Ω
	Impact noise reduction	ISO 717-2	Δ Lw ≥ 22 dB
	Application	EN 1307	Class 33
	Tested flammability standards	EN 45545-2	HL2*
		BS6853	1b
		ASTM E.648 ASTM E.662	Class 1 Pass
	Slip resistance	EN 13893	DS: ≥ 0.30
	Body voltage	EN 1815 / ISO 6356	< 2 kV
	Thermal conductivity	EN 12524	0.08 W/m·K

\*EN45545-2 testing has been carried out on various different substrates/adhesives.

These are the highest achieved results.

For a full overview of specific results on aluminium and plywood bases please ask.

Flotex FR is made to order