









Technical specifications




Coral meets the requirements of EN 1307

Coral move FR

	Total thickness	EN -ISO 24346 / ISO 1765	8 mm
	Roll width	EN-ISO 24341	185 cm (customizable)
	Roll length	EN-ISO 24341	27.5 m (customizable)
	Minimum order quantity		500 m ²
	Total weight	EN -ISO 23997 / ISO 8543	3000 gram/m ²
	Pile installation weight	ISO 8543	750 gram/m ²
	Pile thickness	ISO 1766	5.5 mm
	Pile material		100% polyamide BCF ECONYL [®]
	Light fastness	EN ISO 105/B02	≥ 6
	Electrical resistance	ISO 10965	≥ 10 ⁹ Ω
	Impact noise reduction	EN ISO 717-2	Δ L _w ≥ 28 dB
	Application	EN 1307	Class 32
	Tested flammability standards	EN 45545-2	HL3*

Coral meets the requirements of EN 14041



	Slip resistance	EN 13893	DS: ≥ 0.30
	Body voltage	EN 1815 / ISO 6356	< 2 kV
	Thermal conductivity	EN 12524	0.07 m ² W/m-K

*EN45545-2 testing has been carried out on various different substrates/adhesives.

These are the highest achieved results.

For a full overview of specific results on aluminium and plywood bases please ask.

Coral move FR is made to order