

Introducing

marmoleum^{® with} topshield² ... the floor for the real world. sheet & tile

Because in the real world, **STUFF** happens.

Fortunately, Marmoleum[®] with the new and improved Topshield 2[™] finish is the only resilient flooring with an occupancy-ready finish that can be easily and cost-effectively renewed, bringing the floor back to its original beauty after years of heavy use. Lots of floors and finishes work well in theory, but only Marmoleum® with Topshield 2[™] works well in the real world, where staining agents do not get removed in time, dirt and grit does not get cleaned up regularly, and your non-renewable finish gets permanent stains and scratches.

Marmoleum[®] with Topshield 2[™]

- Occupancy Ready with no initial maintenance required
- Lowest cost of ownership of resilient flooring
- Exceptional performance against soiling, staining, scratching, and scuffing
- Renewable, allowing Marmoleum®'s industry best system service life of 30 years ٠
- Sustainable, water-based technology

Renewable vs. Non-strippable flooring



Cleaning vs. Maintenance

Cleaning is what you do REGULARLY: sweeping, dusting, damp mopping.

Maintenance is the PERIODIC improvements or renovation procedures above and beyond the day-to-day care.

No Maintenance does not mean no cleaning! In fact, if you do not clean, you will have to maintain ANY manufacturer's floor.

Occupancy Ready

Occupancy Ready means that at the time of installation, no maintenance is required.

Cleaning with a treated dust mop, or a damp mop with a neutral detergent is all that is needed at the time of installation.

FLOORING SYSTEMS

Marmoleum[®] with Topshield 2[™]

non-strippable floor covering



sheet & tile

with topshield²

	Topshield 2™	PUR's ²	Rubber	Strippables ³	
Soiling ¹	••••	•••	••	••	key •••• excellent ••• good •• fair • poor
Staining ¹	••••	••••	••	••	
Scuffing	•••	•••	••	••	
Scratching	•••	••			
Slip	•••	•••	•••	••	
Sustainability	••••	••	•••	•	
Life/Cost	••••	••	••	•	

Floor Finish Comparison Chart

1 View the independent, third-party test results online at www.forboflooringNA.com/topshield2

2 typical finish on competitive linoleum

3 typical finish on VCT



Topshield 2[™] construction



- The primary layer acts as a primer that is flexible and elastic. The primer is UV cured creating a strong bond with the Marmoleum[®] surface.
- The secondary layer is a tough surface finish that is dirt repellent and resistant to scratches and staining. With Topshield 2[™], the formulation of both finish layers has been improved, and the topfinish layer is UV cured for even higher performance.





creating better environments