

# sustain 885m

marmoleum® sheet & tile adhesive



## Performance

- Water-based adhesive - 100% solvent free
- Highly Moisture Resistant - 8 lbs. per 1,000 square feet in 24 hours when tested in accordance with the latest version of ASTM F1869, and 85% RH when tested with the latest version of ASTM F2170
- Contains MicroSept™ Anti-Microbial Protection
- CA SCAQMD Rule 1168 Compliant
- Passes Air Quality Regulations per CA Section 01350
- Use a 1/16" x 1/16" x 1/16" Square Notch Trowel
- Spread Rate: Approximately 125 square feet per gallon



## Sustainability

- Contains 20% Post-Consumer Recycled Content
- Packaged in Eco-Pure® biodegradable plastic pails, which decompose naturally in landfills within 1 to 3 years.
- Sustain 885m contributes to LEED™ points in the following categories:
  - EQ Credit 4.1 – low emitting materials
  - MR Credit 4.2 – adhesives made with 20% post-consumer recycled content
  - MR Credit 4.5 – regional materials /jobsites within 500 miles of manufacturing location (Dalton, GA 30735)



EcoPure®  
Biodegradable Plastic Pail

As a leader in sustainability, Forbo believes it is important to provide sustainable product improvements at **no additional cost to the consumer**. As a result, Sustain 885m costs the same as Forbo's competitively priced L885 adhesive.



1-800-842-7839 - United States  
1-866-661-2351 - Canada  
info.na@forbo.com  
www.forboflooringNA.com

creating better environments

sustain (sə-'stān)

forbo

FLOORING SYSTEMS