

Product quick info

EL 0/V10 NP-SE black 2.25

Sketch of cross-section (not actual size)

Applications

- Conveyors without tensioning device
- Cross-belt sorters
- Parcel handling
- Start-stop belts

Properties/Advantages

- Semi-elastic 1 ply hybrid fabric of polyester (special fabric construction)
- Inverted pyramid pattern on top face, high friction on top face
- Very good self-tracking properties, perfect for short center distances and wide belts
- Mechanical fasteners possible ($D_{min} = 40 \text{ mm}$)
- Tension between 1.5% and 5.0%. When belts are supplied with pretension no take-up necessary (cost saving)
- Flame-retardant accord. to EN 20340/ISO 340 and ASTM 378-D

Basic technical data

Top face	Polyvinyl chloride, NP
Underside	Polyester fabric
Article no.	909231
d_{min} [mm]	24
Total thickness [mm]	2.25
k_1 % relaxed [N/mm width]	0.3
Weight [kg/m ²]	2.4
Permitted operating temperature [°C] -10 to +70	

Product Quick Info | EN | 05.2023
FMS - Reproduction of text or parts thereof only
with our approval. Modifications reserved.

Forbo Siegling GmbH
Lilienthalstrasse 6/8, D-30179 Hannover
Phone +49 511 67 04 0
www.forbo-siegling.com, siegling@forbo.com