

eurocol

865

the strong connection



EUOPRIME BLOCK

Blocking primer, for exotic wood, primer for renovation and exotic wood, light, warmtoned wood grain accentuation, water-free.

PRODUCT TYPING

Base	Solved synthetic polymer.
Color	Transparent.
Consistency	Thin liquid.

- Primer, rollable (containing solvents) blocks against wood components and wax residues which might cause problems with lacquer bonding and discoloration.
- Especially for exotic wood, smoked oak.
- Ideal for renovation of old parquet flooring.
- Produces a lightwarm-toned start of the wood surface.
- Dries fast.
- Reduces side gluing.
- Can be applied in 1 - 2 coats, overcoatable with Eurocol parquet lacquers.
- For interior use.
- The product can be used on underfloor heating.
- Observe the protective instructions in the safety data sheet!

PROPERTIES

Consumption	Roller: approx. 110 ml/m ² (per coat).
Flammability	Highly flammable liquid
Frost resistance	yes.
Special quality	Especially parquet flooring from exotic wood.
Specific weight	0.9 kg/l

APPLICATION

For blocking against wood components and wax residues.

PROCESSING

Storage	Store cool and dry in unopened packaging.
Tools	Paint roller.
Waiting time	Minimum 2 hours, maximum 24 hours. *
Shelf Life	Approx 12 months, in unopened packaging. After use close the open packaging well.
Remarks	

865 EUOPRIME BLOCK

* The stated values are laboratory values which, given the large variation in climatological conditions, subfloor compositions and layer thicknesses, are only guideline values.

Substrate:

- The surfaces to be sealed must be clean and free of residues of oil, wax, silicone and other adhesion-reducing layers.
- Joints are closed with suitable Eurocol joint sealant.
- The fine sanding depends on the type of wood. The surface and edge sanding must be levelled with a sanding grid.
- In case of defects, reservations must be made in writing.

Instruction manual:

Before use, temper the product according to the processing conditions.

- Shake well before use!
- Pour the varnish into a Eurocol sealing bucket and use a scraper grid when applying.
- The application must be carried out with a clean, solvent-resistant nylon roller. Roll the coating wet-on-wet in one operation, first crossways and then lengthways to the grain direction.
After drying of the primer (min. 45 minutes), but within 24 hours, a second application is possible on highly absorbent woods.
- When reworking old, sealed multi-layer parquet, sand down to the raw wood. The composition of the primer reduces swelling and possible detachment of the top lamellas during later resealing. However, residues of UV sealers that have not been removed can reduce adhesion. However, no guarantee can be given for the prevention of top lamella peeling.
- After 2 - 3 hours, but within a maximum of 24 hours and after complete drying, overcoat with Eurocol Aqua lacquers.

During application on the prepared parquet floor, use shoe covers for the shoes to avoid footprints.

Ensure even ventilation during the drying process. Avoid draughts and direct sunlight.

In case of dense woods and / or higher humidity the drying time will be longer. In these cases, heating and air exchange must be provided. Processing must be carried out at temperatures at least 5 degrees above dew point.

Working conditions:

Required surrounding temperature: min. 18°C.

Material and subfloor temperature: min. 15°C.

Relative humidity: 35 - 75%, recommended <65%.

ENVIRONMENT AND HEALTH

GISCODE	G2
Safety and environment	Safety data sheets of Forbo Eurocol products according to EEG-guideline 91/155. Keep out of reach of children. Do not eat, drink or smoke while processing the product. Only give completely empty containers for recycling. Bound material residues can be disposed of as household waste.
MSDS	For extensive information about safety and environment we refer to our website www.eurocol.nl .

ITEM DATA

artikel	productname	packaging	shipping unit
865	Europrime Block	PE jerrycan à 10 l	60/pallet

Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed. This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work. The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturer's liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content. As use, processing- and storage conditions on site are beyond manufacturer's influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to be followed by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use.

This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!

BG175603, Version 09, Stand 2019-06-21, ersetzt Ausgabe vom 2017-12-06.

865 EUROPRIME BLOCK