



# Modul'up

## LRV & DSDC product accreditation

Design	Colour number	Colour name	NCS	LRV Y (BS8493)	DSDC Rating*	DSDC Comments*
Modul'up	4380472/43C80472	oak silver	S 5502-Y	25	1b	
	4380421/43C80421	oak polar	S 3502-Y	33	1b	
	4380473/43C80473	oak natural	S 4005-Y20R	32	1b	
	4380483/43C80483	oak scandinave	S 4020-Y20R	29	1b	
	4380233/43C80233	rustic oak cevennes	S 4020-Y30R	34	2	Rated 2 due to stronger groove lines and pattern
	4380232/43C80232	rustic oak amazonie	S 6005-Y20R	24	2	Rated 2 due to stronger groove lines and pattern
	4380213/43C80213	rustic oak yosemite	S 4010-Y30R	30	2	Rated 2 due to stronger groove lines and pattern
	4380212/43C80212	rustic oak yellowstone	S 4502-Y	34	2	Rated 2 due to stronger groove lines and pattern
	4330012/43C30012	terra lead	S 4502-G	27	1b	
	4330001/43C30001	terra dove	S 3500-N	41	1b	
	4330573/43C30573	cement clay	S 3005-Y20R	41	2	
	4330570/43C30570	cement chalk	S 2502-Y	49	X	Rated unsuitable due to speckles
	4330572/43C30572	cement medium grey	S 5005-N	25	2	
	4330113/43C30113	linea sand	S 5010-Y10R	28	2	
	4330121/43C30121	linea light grey	S 4005-Y20R	35	1b	
	4330771/43C30771	concrete silver	S 4500-N	28	1b	
	4330761/43C30761	concrete steel	S 7000-N	16	2	
	4330767/43C30767	resin cobalt	S 3560-R80B	9	1a	
	4330778/43C30778	resin kiwi	S 2070-G60Y	33	1a	
4330756/43C30756	resin saffron	S 2070-Y10R	40	1a		

	<b>2016-074 FORBO FLOORING</b>	
	<b>DSDC RATING KEY</b>	
	<b>NOV-16</b>	
<b>*RATING</b>	<b>*RATING DESCRIPTION</b>	
<b>Class 1a</b>	<p>Flooring within this rating is plain and can be used indiscriminately. That said, bear in mind the need to contrast flooring and walls, skirtings, doors/frames, furniture and sanitary ware.</p> <p>Contrast is the key word.</p> <p>We recommend a minimum contrast of 30 units LRV (Light Reflectance Value) between the critical surfaces mentioned above.</p>	
<b>Class 1b</b>	<p>Flooring within this rating is semi-plain (minimal texture or fleck/pattern, wood effect with no knots) and in general, can be used throughout.</p> <p>Natural patterns such as timber and stone may be used in most areas due to their familiarity but with a degree of caution.</p> <p>Bear in mind minimum contrast of 30 units LRV (Light Reflectance Value) between the critical surfaces mentioned above.</p>	
<b>Class 2</b>	<p>Flooring within this rating has some pattern and needs to be used with caution. The natural patterns such as timber and stone in this range are more figured/patinated and although still familiar they need to be used with more caution than the above range.</p> <p>Bear in mind minimum contrast of 30 units LRV (Light Reflectance Value) between the critical surfaces mentioned above.</p>	

For an environment to be considered 'dementia-inclusive' or 'dementia-friendly', careful consideration must be given to the entire specification, not just the flooring.

As with many design features, individual needs and preferences should also be considered. What is fine for one person, may not be the case for another.

For more information and to download our 'Designing for dementia care' brochure visit [www.forbo-flooring.co.uk/care](http://www.forbo-flooring.co.uk/care)