

		Tiles	Roll
Identification Standard Data according to 1307			
Type of manufacture	ISO 2424	Woven	Woven
Aspect	ISO 2424	Loop pile	Loop pile
Pile fibre composition	ISO 2424	100% Pa 6.6. Ascend® Ultron™	100% Pa 6.6. Ascend® Ultron™
Dye method		Continuous dyed	Continuous dyed
Soil protection		Yes	Yes
Primary backing	ISO 2424	PES	PES
Backing	ISO 2424	TEXtiles® 50 x 50 cm	textile
Dimensions	CEN/TS 14159	(20 tiles per box = 5 m2)	approx. 400 cm width
Roll length			approx 27m
Collection size		15 colourways	5 colourways
Pattern report		-	-
Effective pile thickness	ISO 1766	Approx. 2,50 mm	approx. 2,00 mm
Total thickness	ISO 1765	Approx. 5,00 mm	approx. 3,50 mm
Total pile mass	ISO 2424	Approx. 550 g/m2	approx. 550 g/m2
Total mass	ISO 8543	Approx. 3800 g/m2	approx. 1.900 g/m2
Number of tufts	ISO 1763	Approx 156.000/m2	approx. 156.000 /m2
Effective pile mass	ISO 8543	-	-
Stroll test	ISO 6356	≤2 kV	≤2 kV
Vertical resistance	ISO 10965	-	-
Horizontal resistance	ISO 10965	-	-
Classification for use	EN 1307	33 Commercial – heavy use	33 Commercial – heavy use
Castor chair use		Yes	Yes
Luxury rating	EN 1307	LC1	LC1
Dimension Stability	EN 986	≤ 0,2 %	
Impact sound reduction		ΔLw Approx. 18 dB(A)	approx. 15 dB(A)
Thermal conductivity	ISO 8302	Approx. 0,10 m² K/W	Approx. 0,06 m² K/W
Flammability	EN 13501-1	Bfl – s1	Cfl – s1
Installation method		Quaterturned - Recommended Broadloomed or brick - possible	
GUT marked		Yes	Yes