

Technical specifications

Step meets the requirements of EN ISO 10582 & EN 13845



surestep® fast fit

		Surestep Original FF	Surestep Material/Wood FF
	Total thickness	EN ISO 24346 2.25 mm	2.25 mm
	Thickness wear layer	EN ISO 24340 0.7 mm	0.7 mm
	Commercial very heavy	EN ISO 10582 / EN ISO 13845 Class 34	Class 34
	Light industrial	EN ISO 10582 / EN ISO 13845 Class 43	Class 42
	Collection size	6	6
	Roll width	EN ISO 24341 2.00 m	2.00 m
	Roll length	EN ISO 24341 ≤ 27 m	≤ 27 m
	Total weight	EN ISO 23997 2.30 kg/m ²	2.30 kg/m ²
	Dimension stability	EN ISO 23999 < 0.1%	< 0.1%
	Residual indentation <i>Typical value</i>	EN ISO 24343-1 ≤ 0.10 mm -0.07 mm	≤ 0.10 mm -0.07 mm
	Acoustical impact noise reduction	EN ISO 717-2 13 dB	14 dB
	Castor chair continuous use	ISO 4918 Pass	Pass
	Use in wet areas	EN 13553 Yes	No
	Light fastness	EN ISO 105 B-02 ≥6	≥6
	Flexibility	EN ISO 24344 ø 10 mm	ø 10 mm
	Slip resistance	EN 13845 Annex C ESf	ESf
		EN 13845 Annex D 50.000 revolutions <10% loss Pass	Pass
		AS/NZS 4586:2013 – Ramp R10	R10
		AS/NZS 4586:2013 – Wet Pendulum p3 ⁽¹⁾	p3 ⁽¹⁾
		Surface roughness Rz ≥ 20	≥ 20
	Resistance to chemicals	EN ISO 26987 Very good	Very good
	Creating better environments		
	Renewable electricity	Step is manufactured using 100% electricity made from renewable sources	
	Ska	Step meets Ska Rating criteria for M12 soft floor coverings in office, retail and higher education schemes	

Step safety vinyl meets the requirements of EN 14041

	Product code	EN 14041:2004 0200101-DoP-306	0200101-DoP-306
	Product code	EN 14041:2004 0200101-DoP-GB306	0200101-DoP-GB306
	Reaction to fire	ISO 9239.1 CRF >4.5kW/m ² , Smoke <750%.min	CRF >4.5kW/m ² , Smoke <750%.min
	Body voltage	EN 1815 < 2kV	< 2kV
	Thermal conductivity	EN 12524 0.25 W/m.K	0.25 W/m.K

⁽¹⁾ Wet pendulum values of Forbo safety vinyl have been achieved in an accredited 3rd party laboratory. Forbo will not be liable or responsible for highly variable and varying in situ results.

For the latest installation instructions, please visit www.forbo-flooring.com.au/installation.

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.



Whilst Forbo Floorcoverings Pty Ltd. does its best to ensure that the contents of this specification are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Floorcoverings Pty Ltd. makes no, and expressly disclaims all, guarantees of any kind, express or implied in respect of the information, content, materials or products displayed in this specification and does not represent that the information is accurate, complete or current.

info.au@forbo.com

1800 224 471

forbo-flooring.com.au/step

forbo-flooring.com.au/downloads



FLOORING SYSTEMS

creating better environments