
















Technical specifications

safestep (up to R12)

Safestep meets the requirements of EN 1307

	Total thickness	EN 428 / ISO 1765	2.0 mm
	Roll width	EN 426	200 cm
	Roll length	EN 426	20 - 27 m
	Total weight	EN 430 / ISO 8543	2750 gram/m ²
	Dimensional stability	EN 434 ISO 23999 / ISO 2551	< 0.1%
	Abrasion resistance	EN 660-2 / ISO 24338	≤ 2 mg/mm ³
	Indentation residual	EN 433 / ISO 24343-1	≤ 0.05 mm
	Light fastness	EN ISO 105/B02	≥ 6
	Flexibility	EN 435 / ISO 24344	ø 10 mm
	Resistance to chemicals	EN 423 / ISO 26787	Very good
	Electrical resistance	EN 1081 / ISO 10965	> 1.10°Ω
	Slip resistance	DIN 51130/51131 EN 13845 Annex C	R11, R12 ESf
	Fire resistance	ECE-R 118 / FMVSS 302	Approved
	Personal charging	ISO 6356	< 2 kV
	Heat transmission resistance	EN 12524	0.25 m ² K/W

All countries

Forbo Flooring Systems
High Holborn Road
Ripley
Derbyshire DE5 3NT
UK

Tel: +44 (0) 1773 744121
Fax: +44 (0) 1773 744142

Email: info@forbo-transportflooring.com
www.forbo-flooring/transportation

Registered Office:

Forbo Flooring UK Limited
High Holborn Road, Ripley
Derbyshire DE5 3NT
Registered in England: 9200318