













Technical specifications

coral[®] brush pure

Coral brush pure meets the requirements of EN 1307

	Total thickness	EN 428 / ISO 1765	Approx 9 mm
	Roll width	EN 426	Approx 100/155/205 cm
	Roll length	EN 426	Approx 27.5 m
	Total weight	EN 430 / ISO 8543	Approx 3400 gram/m ²
	Pile installation weight	ISO 8543	Approx 920 gram/m ²
	Pile thickness	ISO 1766	Approx 7 mm
	Pile material	ECONYL [®] 100% regenerated polyamide BCF	
	Dimensional stability	EN 434 ISO 23999 / ISO 2551	Pass
	Light fastness	EN ISO 105/B02	> 5
	Resistance to chemicals	EN 423 / ISO 26787	Very good
	Electrical resistance	EN 1081 / ISO 10965	hor. $1.1 \times 10^{11} \Omega$, vert. $3.1 \times 10^{10} \Omega$
	Slip resistance	EN 13893	$\mu = 0.51$
	Fire resistance	ECE-R 118 / FMVSS 302	EN 13501-1: B _{f1} -s1
	Personal charging	ISO 6356	< 2 kV
	Heat transmission resistance	EN 12524	ISO 8302: 0.118 m ² K/W

All countries

Forbo Flooring Systems
 High Holborn Road
 Ripley
 Derbyshire DE5 3NT
 UK
 Tel: +44 (0) 1773 744121
 Fax: +44 (0) 1773 744142
 Email: info@forbo-transportflooring.com
www.forbo-flooring/transportation

Registered Office:

Forbo Flooring UK Limited
 High Holborn Road, Ripley
 Derbyshire DE5 3NT
 Registered in England: 9200318