










Technical specifications

flotex[®] FR

Flotex FR meets the requirements of EN 1307

	Total thickness	ISO 1765	Approx 3.3 mm
	Roll width	EN 426	200 cm
	Roll length	EN 426	30 m
	Light fastness	EN ISO 105/B02	6
	Pile material		100% polyamide
	Dimensional stability	ISO 2551	≤ 0.20%
	Total weight	ISO 8543	Approx 1225 gram/m ²
	Pile installation weight	ISO 8543	Approx. 250 gram/m ²
	Pile thickness	ISO 1766	Approx 2 mm
	Electrical resistance	EN 10965	Approx. 10 ¹⁰ Ω
	Contact sound insulation	ISO 140-8	Δ Lw = approx. 22 dB

Flotex FR product meets the demands set by EN 14041

	Slip resistance	EN 13893	> 0.30
	Personal charging	ISO 6356	< 2 kV

EC declaration of conformity

IMO Resolution A653(16)

IMO Resolution MSC 307(88) Annex 1 Part 2

IMO Resolution MSC 307(88) Annex 1 Part 5

US Coast Guard approval ref: 164.117/1121/WCL MED0364

All countries

Forbo Flooring Systems
High Holborn Road
Ripley
Derbyshire DE5 3NT
UK
Tel: +44 (0) 1773 744121
Fax: +44 (0) 1773 744142
Email: info@forbo-transportflooring.com
www.forbo-flooring/transportation

Registered Office:

Forbo Flooring UK Limited
High Holborn Road, Ripley
Derbyshire DE5 3NT
Registered in England: 9200318