























Technical specifications

Accord carpet tiles meet the requirements of EN 1307

| Description | Tufted multi-pile height loop carpet tile | |
|--|---|---|
|  Tile size | EN 994 | 50 cm x 50 cm |
|  Total thickness | ISO 1765 | 6.4 mm |
| Pile height | ISO 1766 | 3 mm |
|  Collection size | 12 | |
| Packaging per carton tiles | 16 (4 m ²) | |
|  Commercial use | EN ISO 10874 | Class 33 |
| Pile composition | 100% polyamide 6 | |
| Dye method | 100% solution dyed | |
| Stitch density | ISO 1763 | 207,821 per m ² |
|  Pile weight | ISO 8543 | 605 g/m ² |
| Total weight | ISO 8543 | 4145 g/m ² |
|  Primary backing | Polyester | |
| Secondary backing | ProBac™ modified bitumen and polyester fleece. Contains over 76% recycled content. Available in SOFTbac® secondary backing. | |
|  Acoustical impact noise reduction | ISO 10140-3 | 24 dB |
|  Acoustical sound absorption | ISO 354 | $\alpha_w = 0.15$ (H) |
|  Castor chair continuous use | ISO 4918 | $r \geq 2.4$ |
|  Colour fastness to light | EN ISO 105-B02 | ≥ 5 |
|  Dimensional stability | EN 986 | ≤ 0.2 % |
|  Indoor air emissions: TVOC after 28 days | EN 16516 | ≤ 0.1 mg/m ³ |
|  Creating Better Environments Renewable Energy | All Tessera carpet tiles are manufactured using 100% renewable energy (electricity & biogas) | |
|  Recycled Content | Accord carpet tiles contain 61% recycled content by weight | |
|  Indoor Air Quality | Accord carpet tiles comply to 01350 Indoor Air Quality Standard | |
| Ska Rating | Accord meets Ska Rating criteria for M12 soft floor coverings in office, retail and higher education schemes | |
|  Installation method | Monolithic | |
| Accord carpet tiles meet the requirements of EN 14041:2004 | | |
|  CE | EN 14041 | |
|  Product code | EN 14041 | 1170104-DoP-210 |
|  Reaction to fire | ISO 9239.1 | CRF>2.2 kW/m ² , Smoke development <750%.min |
|  Slip resistance | AS 4586 | R12 |
|  Body voltage | ISO 6356 | ≤ 2.0 kV |
|  Thermal conductivity | EN 12667 | 0.06 W/mK |



All Forbo Flooring Systems' sales organisations and manufacturing sites worldwide have certified Quality Management Systems in accordance with ISO 9001. All Forbo Flooring Systems' manufacturing plants have certified Environmental Management Systems in accordance with ISO 14001. Tessera Accord carpet tiles are manufactured in a facility certified to SA8000® and ISO 45001. The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental product declarations (EPDs).

For more information:

 info.au@forbo.com

 1800 224 471

 forbo-flooring.com.au/tessera

 forbo-flooring.com.au/downloads



FLOORING SYSTEMS

creating better environments