

# Technical specifications

Eternal Digital Print meets the requirements of EN-ISO 10582



	Total thickness	EN-ISO 24346	2,0 mm
	Wear layer thickness	EN-ISO 24340	0,7 mm
	Collection size		4
	Commercial use	EN-ISO 10874	34 very heavy
	Industrial use	EN-ISO 10874	43 heavy
	Roll width	EN-ISO 24341	*
	Roll length	EN-ISO 24341	*
	Total weight	EN-ISO 23997	2,8 kg/m <sup>2</sup>
	Dimensional stability	EN-ISO 23999	< 0,1 %
	Residual indentation	EN-ISO 24343-1	≤0,05, typical value 0,03
	Abrasion resistance	EN 660-2	group T
	Castor chair continuous use	ISO 4918 / EN 425	no effect
	Light fastness	ISO 105-B02	≥ 6
	Flexibility	EN-ISO 24344	∅ 10 mm
	Resistance to chemicals	EN-ISO 26987	very good
	Slip resistance	DIN 51130	R10
	Electrical resistance	EN 1081	R1 > 1·10 <sup>9</sup> Ω

EN 14041



0200105\_DoP-306

All Eternal products meet the requirements of EN 14041

	Reaction to fire	EN 13501-1	B <sub>fl</sub> -s1
	Slip resistance	EN 13893	DS - μ ≥ 0,30
	Body voltage	EN 1815	≤ 2 kV
	Thermal conductivity	EN 12524	0,25 W/m·K

*	design width	design length
Rainbow	195 cm	1000 cm
excl ± 25 mm white margin around		
Magnified Nature		
colourful geode	min. 195 cm, max. 395 cm	min. 257 cm, max. 521 cm
natural geode	min. 195 cm, max. 395 cm	min. 222 cm, max. 450 cm
petrified bark	min. 195 cm, max. 395 cm	min. 222 cm, max. 450 cm
delivered on white background with ± 25 mm margin around		

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.  
 All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.  
 The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.

