

siegling transilon



Product quick info

PVC150 OFR CxF-NA royal blue FDA



Sketch of cross-section (not actual size)

Applications

- Fruit and vegetable processing
- Primary agricultural processing
- Processing of oily and fatty food
- Horizontal conveying (metering)
- Troughed conveyors
- Utility agriculture harvesting
- Fish, meat and seafood processing

Properties/Advantages

- Robust
- Excellent abrasion resistance (top coating thickness 1 mm)
- Superior resistance to oil and grease
- Troughable
- Easy-to-clean underside supports hygiene concepts
- UV-C resistant
- Color: Signal Blue (similar to RAL 5005)
- Not antistatic
- Complies to FDA regulations for direct contact to foodstuffs

Basic technical data

Top face	Polyvinyl chloride, smooth
Underside	Polyvinyl chloride, fabric
Article no.	908146
d _{min} [mm]	40
Total thickness [mm]	4.06
k _{1%} relaxed [N/mm width]	9.5
Weight [kg/m²]	4.88

Permitted operating temperature [°C] -18 to +82

Product Quick Info | EN | 08.2023 FMS · Reproduction of text or parts thereof only with our approval. Modifications reserved.

Forbo Siegling GmbH Lilienthalstrasse 6/8, D-30179 Hannover Phone +49 511 67 04 0 www.forbo-siegling.com, siegling@forbo.com

