

eurocol

872

the strong connection



SURFACE FINISH ADDITIVE R10

Lacquer additives,
achieves slip class R10 with surface finish.

PRODUCT TYPING

Base	Ceramic powder.
Color	White.
Consistency	Powder.

- Additives to achieve the slip class R10 according to German BGR 181.
- For addition in approved and tested Eurocol Surface Finish products.

PROPERTIES

Flammability	Non-flammable.
Frost resistance	yes.
Special quality	Evaluation group R10 in combination with surface laquer..
Specific weight	1,1 g/cm ³ .

APPLICATION

Additive for Eurocol Surface Finish.

PROCESSING

Storage	Store cool and dry in unopened packaging.
Mixing ratio	3%, 155 g/5 l Surface finish laquer.
Shelf Life	Approx 36 Months, in unopened packaging.
Remarks	Observe the technical information and safety data sheets of any laying materials used! Not suitable for conductive floor coverings.TODO

** The stated values are laboratory values which, given the large variation in climatological conditions, subfloor compositions and layer thicknesses, are only guideline values.*

Instruction manual:

- Temper the product. Shake component A in the original container well and empty it completely into a clean plastic mixing container.
- To produce the slip class R10, add the Eurocol 872 Surface finish Additive R10 to the appropriate Eurocol surface finish product and mix it thoroughly by stirring in slowly, then add the hardener.
- To achieve the slip class R10, 3% of the Eurocol 872 Surface finishing additive needs to be added.
- Add the hardener component B by stirring completely to the premix of the component A and additives. Stir the components for at

872 SURFACE FINISH ADDITIVE R10

Forbo Eurocol Nederland B.V. | Industrieweg 1-2 | Postbus 130 | 1520 AC Wormerveer | Tel: +31 (0)75 627 16 00 | info.eurocol@forbo.com
Forbo Eurocol Deutschland GmbH | August-Röbling-Straße 2 | DE - 99091 Erfurt | PF 80 02 53 | Telefon: +49 361 730 41 0 | info.eurocol.de@forbo.com
ООО Форбо Еврокол Рус | Россия, г. Старый Оскол | Тел. +7 495 2152101 | info.eurocol.ru@forbo.com

Eurocol is part of the Forbo Group



- least three minutes with an electric mixer to a homogeneous mixture. Let the mixture rest for 10 minutes then stir again briefly.
- Apply the coating evenly, acc. To the processing instructions of the surface finishing products used. Apply surface finishing additives R10 only in the last coat of the lacquering system.
- When applying it on the floor, use shoe covers to avoid footprints.
- The mixture of the additives must be processed within the pot life. Keep stirring the mixture regularly.

ENVIRONMENT AND HEALTH

Safety and environment	Safety data sheets of Forbo Eurocol products according to EEG-guideline 91/155. Keep out of reach of children. Do not eat, drink or smoke while processing the product. Only give completely empty containers for recycling. Bound material residues can be disposed of as household waste.
MSDS	For extensive information about safety and environment we refer to our website www.eurocol.nl .

ITEM DATA

artikel	productname	packaging	shipping unit
872	Surface Finish Additive R10	PE bottle à 0,31 kg	720/pallet

Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed. This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work. The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturers liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content. As use, processing- and storage conditions on site are beyond manufacturers influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to be followed by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use.

This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!

872 SURFACE FINISH ADDITIVE R10